



Especificaciones

Especificación	Valor
No./mount. holes [qty.]	2 qty
O.1 [mm]	119.5 mm
No./mount. holes with thread [qty.]	1 qty
L.1 [mm]	200 mm
Rotation	CW
Size A [mm]	74 mm
Size B [mm]	10 mm
No./teeth	8 qty
No./teeth (fits into) [qty.]	8 qty
Power	1.1 kW
C.1 [mm]	M10x1.5 mm
Voltage	12 V
C.2 [mm]	12.50 mm

Aplicaciones

Marca
CHRYSLER

Código original

0001107415	0001107432
05033556AB	17790

Código equivalente (Fabricante del vehículo)

113613 (CARGO)	F032113613 (CARGO)
17790N (WAI / TRANSP0)	17790R (WAI / TRANSP0)
17821N (WAI / TRANSP0)	17822N (WAI / TRANSP0)
20401213RC (REAL)	22.3208 (LAUBER)
25-3165 (ELSTOCK)	254234 (KUHNER)
05033556AB (CHRYSLER)	05033556AC (CHRYSLER)
4793493 (CHRYSLER)	5033133AA (CHRYSLER)
5033133AB (CHRYSLER)	5033133AC (CHRYSLER)
5033556AC (CHRYSLER)	6010312 (SANDO)
CST10312RS (CASCO)	MAV123120 (SIOM)
S0102 (AS-PL)	S1038B (PRESTOLITE)
STR50424 (WOODAUTO)	PRSL781 (3EFFE)
STRL781 (3EFFE)	331844 (LOGISTIK)
STR1237 (ELECTROLOG)	STR1390 (ELECTROLOG)
STX201237 (STARDAX)	STX201237R (STARDAX)
830.563.082.010 (PSH)	830.563.082.440 (PSH)
830.563.082.460 (PSH)	S135.453 (PSH)