



Especificaciones

Especificación	Valor
No./mount. holes [qty.]	3 qty
O.1 [mm]	126 mm
No./mount. holes with thread [qty.]	0 qty
L.1 [mm]	316 mm
Rotation	CW
Size A [mm]	92 mm
Size B [mm]	47.5 mm
No./teeth	10 qty
Power	4 kW
O.3 [mm]	126 mm
Oil sealed	Yes
O.2 [mm]	126 mm
C.1 [mm]	14.00 mm
Voltage	12 V
C.3 [mm]	14.00 mm
C.2 [mm]	14.00 mm

Aplicaciones

Marca
INTERNATIONAL

Código original

18406	2-2356-ND-1
228000-5600	228000-8510

Código equivalente (Fabricante del vehículo)

18406N (WAI / TRANSPO)	18406R (WAI / TRANSPO)
190-30100 (ROBERT'S)	193432A1 (CASE)
193432A2 (CASE)	20432123BN (REAL)
20432123OE (REAL)	20432452BN (REAL)
20432452OE (REAL)	246-30118 (DIXIE)
S-8854 (DIXIE)	254667 (KUHNER)
3283813 (CUMMINS)	3283815 (CUMMINS)
3675245RX (CUMMINS)	3675246RX (CUMMINS)
3675288RX (CUMMINS)	3920328 (CUMMINS)
3957589 (CUMMINS)	3957590 (CUMMINS)
6040254.0 (SANDO)	6040254.1 (SANDO)
6040321.0 (SANDO)	6040321.1 (SANDO)
87413501 (NEW HOLLAND)	88213771 (POWERMAX)
91-29-5449 (WILSON)	91-29-5449N (WILSON)
CST40254AS (CASCO)	CST40254GS (CASCO)
CST40321.AS (CASCO)	CST40321.GS (CASCO)
SG9103 (GHIBAUDI)	STN8510 (KRAUF)
STR70340 (WOODAUTO)	S6333S (AS-PL)
UD16533S (AS-PL)	STR6429 (ELECTROLOG)
STX210082 (STARDAX)	