



Especificaciones

Especificación	Valor
No./mount. holes [qty.]	3 qty
O.1 [mm]	89 mm
No./mount. holes with thread [qty.]	0 qty
L.1 [mm]	279 mm
Rotation	CW
Size A [mm]	89 mm
Size B [mm]	47.5 mm
No./teeth	10 qty
Power	4.8 kW
O.3 [mm]	89 mm
O.2 [mm]	127 mm
C.1 [mm]	11.50 mm
Voltage	12 V
C.3 [mm]	11.50 mm
C.2 [mm]	11.50 mm

Aplicaciones

Marca	Vehículo
JOHN	DEERE

Código original

428000-5740	428000-7340
RE537515	

Código equivalente (Fabricante del vehículo)

20432884BN (REAL)	20432884OE (REAL)
246-31112 (DIXIE)	S-80600 (DIXIE)
256300D (KUHNER)	6040488.0 (SANDO)
6040488.1 (SANDO)	AI-80085 (AINDE)
CST40488AS (CASCO)	CST40488GS (CASCO)
RE537515 (JOHN DEERE)	RE539696 (JOHN DEERE)
RE541093 (JOHN DEERE)	RE548692 (JOHN DEERE)
RE548694 (JOHN DEERE)	RE549229 (JOHN DEERE)
SE502558 (JOHN DEERE)	STN4740 (KRAUF)
S6427S (AS-PL)	UD18559S (AS-PL)
630.533.103.050 (PSH)	630.533.103.260 (PSH)
S134.098 (PSH)	S144.028 (PSH)
S12DE0708A2 (SIDAT)	5040636 (MEAT & DORIA)
STR6323 (ELECTROLOG)	1906387 (CUMMINS)