



Especificaciones

Especificación	Valor
No./mount. holes [qty.]	3 qty
O.1 [mm]	113 mm
No./mount. holes with thread [qty.]	3 qty
L.1 [mm]	225.5 mm
Rotation	CW
Size A [mm]	82 mm
Size B [mm]	6 mm
No./teeth	10 qty
Power	1.2 kW
O.3 [mm]	67 mm
O.2 [mm]	71 mm
C.1 [mm]	M10x1.5 mm
Voltage	12 V
C.3 [mm]	M10x1.5 mm
C.2 [mm]	M10x1.5 mm

Aplicaciones

Marca
CHRYSLER

Código original

19025	4608800AB
M008T88578	MOT21171

Código equivalente (Fabricante del vehículo)

04608800AA (CHRYSLER)	04608800AD (CHRYSLER)
04801651AA (CHRYSLER)	4608800AA (CHRYSLER)
4608800AB (CHRYSLER)	4608800AC (CHRYSLER)
19025N (WAI / TRANSPO)	20437902 (REAL)
25-4390 (ELSTOCK)	255079 (KUHNER)
3756 (CEVAM)	6035209 (SANDO)
830.906.103 (PSH)	S135.870 (PSH)
CST35209AS (CASCO)	LRS02717 (LUCAS)
LRS2717 (LUCAS)	S-80366 (DIXIE)
STM4011 (KRAUF)	STRS414 (3EFFE)
STRS452 (3EFFE)	S5341S (AS-PL)
UD20394S (AS-PL)	S12MH0746A2 (SIDAT)
STX210328 (STARDAX)	STX210328R (STARDAX)
STX210336 (STARDAX)	STX210336R (STARDAX)