



Especificaciones

Especificación	Valor
No./mount. holes [qty.]	3 qty
O.1 [mm]	113 mm
No./mount. holes with thread [qty.]	2 qty
L.1 [mm]	217.5 mm
Rotation	CW
Size A [mm]	82 mm
Size B [mm]	8.5 mm
No./teeth	10 qty
Power	1.2 kW
O.3 [mm]	67.5 mm
O.2 [mm]	70.5 mm
C.1 [mm]	M10x1.5 mm
Voltage	12 V
C.3 [mm]	8.50 mm
C.2 [mm]	M10x1.5 mm

Aplicaciones

Marca	Vehículo	Tipos de modelo	Desde	Hasta
DODGE	Stratus 2.7		01/2001	12/2006
CHRYSLER	SEBRING (JR) 2.7 V6 24V	EER	04/2001	06/2007
CHRYSLER	SEBRING Convertible (JR) 2.7 V6 24V	EER	04/2001	06/2007
CHRYSLER	SEBRING (JR) 2.7 V6 24V	EES	04/2001	06/2007
CHRYSLER	SEBRING Convertible (JR) 2.7 V6 24V	EES	04/2001	06/2007

Código original (Fabricante del vehículo)

04606875AE	4606875AE
17929N	17929R
830.935.103	830.935.103.138
830.935.103.460	S135.753
M000T91881	M000T91881 (MITSUBISHI)
M000T91881ZC	M000T91881ZC (MITSUBISHI)
M0T91881	M0T91881 (MITSUBISHI)
M0T91881ZC	M0T91881ZC (MITSUBISHI)
S-80035	STM3775
STRF520	UD20397S

Código equivalente (Fabricante del vehículo)

04606875AE (CHRYSLER)	4606875AE (CHRYSLER)
17929N (WAI / TRANSPO)	17929R (WAI / TRANSPO)
830.935.103 (PSH)	830.935.103.138 (PSH)
830.935.103.460 (PSH)	S135.753 (PSH)
S-80035 (DIXIE)	STM3775 (KRAUF)
STRF520 (3EFFE)	UD20397S (AS-PL)