



Especificaciones

Especificación	Valor
No./teeth	9 qty
Power	1.4 kW
No./mount. holes [qty.]	2 qty
O.1 [mm]	94 mm
No./mount. holes with thread [qty.]	2 qty
C.1 [mm]	M10x1.25 mm
L.1 [mm]	198 mm
Voltage	12 V
Rotation	CW
C.2 [mm]	M10x1.25 mm
Size A [mm]	70 mm
Size B [mm]	28 mm

Aplicaciones

Marca	Vehículo	Tipos de modelo	Desde	Hasta
mitsubishi	LANCER VIII (CY_A, CZ_A) 2.0 i Ralliart 4WD (CY4A)	4B11-T/C		
mitsubishi	LANCER VIII Sportback (CX_A) 2.0 Ralliart 4WD (CX4A)	4B11-T/C		
mitsubishi	LANCER VIII (CY_A, CZ_A) EVO X - FQ400 (CZ4A)	4B11-T/C	05/2009	12/2010
mitsubishi	LANCER VIII (CY_A, CZ_A) EVO X (CZ4A)	4B11-T/C	06/2008	12/2015
mitsubishi	LANCER VIII (CY_A, CZ_A) EVO X (CZ4A)	4B11-T/C	10/2007	10/2008

Código original (Fabricante del vehículo)

1810A123	1810A123 (MITSUBISHI)
M000T22871	M000T22871 (MITSUBISHI)
M00T22871	M00T22871 (MITSUBISHI)
M0T22871	M0T22871 (MITSUBISHI)
UD100720S	CST35375AS
12460	25-5176
LRS04014	LRS4014
88215139	150.913.092.130
150.913.092.138	S130.211
20437573BN	6035375.0
MAV373750A	19105N
91-27-3460	

Código equivalente (Fabricante del vehículo)

UD100720S (AS-PL)	CST35375AS (CASCO)
12460 (EAI)	25-5176 (ELSTOCK)
LRS04014 (LUCAS)	LRS4014 (LUCAS)
88215139 (POWERMAX)	150.913.092.130 (PSH)
150.913.092.138 (PSH)	S130.211 (PSH)
20437573BN (REAL)	6035375.0 (SANDO)
MAV373750A (SIOM)	19105N (WAI / TRANSPON)
91-27-3460 (WILSON)	