



Especificaciones

Especificación	Valor
No./mount. holes [qty.]	3 qty
O.1 [mm]	127 mm
No./mount. holes with thread [qty.]	0 qty
L.1 [mm]	288 mm
Rotation	CW
Size A [mm]	89 mm
Size B [mm]	28 mm
No./teeth	12 qty
Power	5 kW
O.3 [mm]	93 mm
O.2 [mm]	81 mm
C.1 [mm]	10.50 mm
Voltage	24 V
C.3 [mm]	10.50 mm
C.2 [mm]	10.50 mm

Aplicaciones

Marca
MAN

Código original

30291	51262017263
M008T63271	M8T63271

Código equivalente (Fabricante del vehículo)

MITM8T63271 (WOODAUTO)	PREM85R3005SE (WOODAUTO)
STR71352 (WOODAUTO)	255470 (KUHNER)
255470M (KUHNER)	551.548.123.130 (PSH)
551.548.123.136 (PSH)	551.548.123.138 (PSH)
551.548.123.370 (PSH)	S133.534 (PSH)
S145.052 (PSH)	CST35657AS (CASCO)
CST35657GS (CASCO)	45-5334 (ELSTOCK)
51262017263 (MAN)	LRS04171 (LUCAS)
LRS4171 (LUCAS)	11.139.219 (ISKRA / LETRIKA)
AZE4710 (ISKRA / LETRIKA)	IS9517 (ISKRA / LETRIKA)
72524874 (MAHLE)	MS1035 (MAHLE)
M85405 (PRESTOLITE)	M85R3005SE (PRESTOLITE)
30291N (WAI / TRANSPO)	8067 (CEVAM)
336563 (LOGISTIK)	20437756BN (REAL)
20437756OE (REAL)	6035657.0 (SANDO)
6035657.1 (SANDO)	PRSF355 (3EFFE)
STRF355 (3EFFE)	STM7123 (KRAUF)
CGB-21044 (AINDE)	DRS1044 (DELCO)
S5239S (AS-PL)	UD13180S (AS-PL)
UD19642S (AS-PL)	STR5464 (ELECTROLOG)