



Especificaciones

| Especificación                        | Valor    |
|---------------------------------------|----------|
| No./mount. holes [ qty. ]             | 3 qty    |
| O.1 [ mm ]                            | 119 mm   |
| No./mount. holes with thread [ qty. ] | 0 qty    |
| L.1 [ mm ]                            | 347 mm   |
| Rotation                              | CW       |
| Size A [ mm ]                         | 100 mm   |
| Size B [ mm ]                         | 58 mm    |
| No./teeth                             | 12 qty   |
| No./teeth (fits into) [ qty. ]        | 12 qty   |
| Power                                 | 7 kW     |
| O.3 [ mm ]                            | 119 mm   |
| O.2 [ mm ]                            | 136.5 mm |
| C.1 [ mm ]                            | 13.00 mm |
| Voltage                               | 24 V     |
| C.3 [ mm ]                            | 13.00 mm |
| C.2 [ mm ]                            | 13.00 mm |

Aplicaciones

| Marca      |
|------------|
| MITSUBISHI |

Código original

|            |          |
|------------|----------|
| M005T55172 | M9T80572 |
| ME441057   |          |

Código equivalente (Fabricante del vehículo)

|                       |                      |
|-----------------------|----------------------|
| 151.523.123.130 (PSH) | 19081048 (DELCO)     |
| DRS0322 (DELCO)       | 20437066OE (REAL)    |
| 255644 (KUHNER)       | 6035660 (SANDO)      |
| CST35660 (CASCO)      | CST35660AS (CASCO)   |
| CST35660ES (CASCO)    | CST35660GS (CASCO)   |
| CST35660OS (CASCO)    | CST35660RS (CASCO)   |
| STRF398 (3EFFE)       | STR5266 (ELECTROLOG) |