



Especificaciones

Especificación	Valor
No./mount. holes [qty.]	4 qty
O.1 [mm]	140.4 mm
No./mount. holes with thread [qty.]	3 qty
L.1 [mm]	174 mm
Rotation	CW
Size B [mm]	20 mm
No./teeth	11 qty
C.4 [mm]	M10x1.5 mm
Power	1 kW
O.3 [mm]	136 mm
O.2 [mm]	153 mm
C.1 [mm]	M10x1.5 mm
Voltage	12 V
C.3 [mm]	M10x1.5 mm
C.2 [mm]	8.00 mm

Aplicaciones

Marca
NISSAN

Código original

23300-0557R	ESW1012
ESW10E7	

Código equivalente (Fabricante del vehículo)

S3178S (AS-PL)	UD14914S (AS-PL)
PRSS553 (3EFFE)	STRS553 (3EFFE)
CGB-54487 (AINDE)	AEX1188 (AUTOELECTRO)
AEY3814 (AUTOELECTRO)	115629 (CARGO)
F032115629 (CARGO)	CST15278AS (CASCO)
CST15278GS (CASCO)	3098 (CEVAM)
DRS0885 (DELCO)	DS1995 (DELCO)
12266 (EAI)	25-4487 (ELSTOCK)
220790 (ERA)	220791 (ERA)
GS438279-A (GPARTS)	GS438279V-R (GPARTS)
CS1582 (HC PARTS)	STV4382 (KRAUF)
254739 (KUHNER)	254739V (KUHNER)
LRS03814 (LUCAS)	LRS3814 (LUCAS)
M000T46571ZT (MITSUBISHI)	M0T46571ZT (MITSUBISHI)
23300-00Q3D (NISSAN)	23300-0557R (NISSAN)
23300-0779R (NISSAN)	23300-1071R (NISSAN)
23300-3307R (NISSAN)	23300-3847R (NISSAN)
23300-7970R (NISSAN)	23300-9161R (NISSAN)
88214550 (POWERMAX)	570.568.114.000 (PSH)
570.568.114.340 (PSH)	570.568.114.341 (PSH)
570.568.114.346 (PSH)	570.568.114.440 (PSH)
570.568.114.500 (PSH)	570.568.114.503 (PSH)
570.568.114.505 (PSH)	S133.875 (PSH)
20479872BN (REAL)	20479872OE (REAL)
6015278.0 (SANDO)	6015278.1 (SANDO)
MAV172780 (SIOM)	MAV172780A (SIOM)
31247N (WAI / TRANSP0)	31247N-OE (WAI / TRANSP0)
STR54177 (WOODAUTO)	VAL438279 (WOODAUTO)
VALESW10E7 (WOODAUTO)	8EA011611-661 (HELLA)
STR00038 (ELECTROLOG)	332252 (LOGISTIK)
233001071 (RENAULT)	4539067500 (RENAULT)
4159064700 (MERCEDES)	A4159064700 (MERCEDES)
A4539067500 (MERCEDES)	4539064700 (SMART)
4539065400 (SMART)	A4539064700 (SMART)
A4539065400 (SMART)	STX210317 (STARDAX)
STX210317R (STARDAX)	ASM1648 (APEC)
NPANSM1648 (NAPA)	14130193 (AES)
42005001 (HERTH+BUSS)	