



Especificaciones

Especificación	Valor
No./mount. holes [qty.]	3 qty
O.1 [mm]	66 mm
No./mount. holes with thread [qty.]	2 qty
L.1 [mm]	225 mm
Rotation	CW
Size A [mm]	76 mm
Size B [mm]	16 mm
No./teeth	10 qty
Power	1.4 kW
O.3 [mm]	104 mm
O.2 [mm]	71 mm
C.1 [mm]	M10x1.5 mm
Voltage	12 V
C.3 [mm]	10.00 mm
C.2 [mm]	M10x1.5 mm

Aplicaciones

Marca	Vehículo	Desde	Hasta
MERCURY	Tracer 1.9	01/1991	12/1996
MERCURY	Tracer 2.0	01/1997	12/1999
FORD	Escort 1.9	01/1991	12/1996
FORD	Escort 2.0	01/1997	12/2002

Código original (Fabricante del vehículo)

3217N	3217R
91-02-5850	91-02-5850N
F0CF-11000-BA	F0CF-11000-BA (FORD)
F0CFBA	F0CFBA (FORD)
F0CU-11000-BA	F0CU-11000-BA (FORD)
F0CUBA	F0CUBA (FORD)
F3JL-11000-AA	F3JL-11000-AA (FORD)
F7PU-11000-LA	F7PU-11000-LA (FORD)
F7PULA	F7PULA (FORD)
F7PZ-11002-LA	F7PZ-11002-LA (FORD)
F7PZLA	F7PZLA (FORD)
S-2063	STF6645
STR82430	UD20605S
880.533.103.519	880.533.103.608
880.533.103.945	STR8953

Código equivalente (Fabricante del vehículo)

3217N (WAI / TRANSPO)	3217R (WAI / TRANSPO)
91-02-5850 (WILSON)	91-02-5850N (WILSON)
S-2063 (DIXIE)	STF6645 (KRAUF)
STR82430 (WOODAUTO)	UD20605S (AS-PL)
880.533.103.519 (PSH)	880.533.103.608 (PSH)
880.533.103.945 (PSH)	STR8953 (ELECTROLOG)