

Especificaciones

Especificación	Valor
No./mount. holes [qty.]	3 qty
O.1 [mm]	91 mm
No./mount. holes with thread [qty.]	1 qty
L.1 [mm]	208.5 mm
Rotation	CW
Size B [mm]	13.5 mm
No./teeth	15 qty
Power	1.8 kW
O.3 [mm]	74.5 mm
O.2 [mm]	123.5 mm
C.1 [mm]	8.50 mm
Voltage	12 V
C.3 [mm]	M8x1.25 mm
C.2 [mm]	8.50 mm

Aplicaciones

Marca
npEl

Código original

31509	3640163
438296	458723

Código equivalente (Fabricante del vehículo)

11090367 (EUROTEC)	12329 (EAI)
1614016380 (PEUGEOT)	1628564780 (PEUGEOT)
9674077280 (PEUGEOT)	20479692 (REAL)
220.538.153 (PSH)	S131.587 (PSH)
S144.016 (PSH)	25-5088 (ELSTOCK)
255610V (KUHNER)	31509N (WAI / TRANSPO)
31509N-OE (WAI / TRANSPO)	3280 (CEVAM)
3640163 (OPEL)	95525945 (OPEL)
42438296 (HERTH+BUSS)	6015296 (SANDO)
AEY3925 (AUTOELECTRO)	CST15296 (CASCO)
CST15296AS (CASCO)	CST15296ES (CASCO)
CST15296GS (CASCO)	CST15296OS (CASCO)
CST15296RS (CASCO)	DRS1088 (DELCO)
DS2198 (DELCO)	LRS03925 (LUCAS)
LRS3925 (LUCAS)	STRE457 (3EFFE)
STV9931 (KRAUF)	S3182S (AS-PL)
UD90375S (AS-PL)	VAL438296 (WOODAUTO)
STR00346 (ELECTROLOG)	S12VA0615 (SIDAT)
S12VA0615A2 (SIDAT)	332198 (LOGISTIK)
5015884 (MEAT & DORIA)	STX210275 (STARDAX)
STX210275R (STARDAX)	