



Especificaciones

Especificación	Valor
No./mount. holes [qty.]	3 qty
O.1 [mm]	90 mm
No./mount. holes with thread [qty.]	0 qty
L.1 [mm]	289 mm
Rotation	CW
Size A [mm]	88.5 mm
Size B [mm]	46 mm
No./teeth	11 qty
Power	2.7 kW
O.3 [mm]	90 mm
O.2 [mm]	127 mm
C.1 [mm]	11.00 mm
Voltage	12 V
C.3 [mm]	11.00 mm
C.2 [mm]	11.00 mm

Aplicaciones

Marca
BOBCAT

Código original

18486	600189
6685190	TM000A28901

Código equivalente (Fabricante del vehículo)

113727 (CARGO)	F032113727 (CARGO)
18486N (WAI / TRANSPO)	254156 (KUHNER)
254156V (KUHNER)	6032116 (SANDO)
60321160 (SANDO)	60321161 (SANDO)
6676957 (BOBCAT)	6685190 (BOBCAT)
7283321 (BOBCAT)	DSL6676957 (BOBCAT)
DSL6685190 (BOBCAT)	8148 (CEVAM)
8213517 (POWERMAX)	88213517 (POWERMAX)
830.549.113 (PSH)	830.549.113.050 (PSH)
830.549.113.120 (PSH)	830.549.113.260 (PSH)
830.549.113.360 (PSH)	830.549.113.440 (PSH)
830.549.113.441 (PSH)	830.549.113.460 (PSH)
830.549.113.510 (PSH)	S135.392 (PSH)
S144.356 (PSH)	9162901 (MAGNETON)
CGB-28901 (AINDE)	CST32116 (CASCO)
CST32116AS (CASCO)	CST32116ES (CASCO)
CST32116GS (CASCO)	CST32116OS (CASCO)
CST32116RS (CASCO)	DRS0104 (DELCO)
MAV341160 (SIOM)	P6685190 (AS-PL)
S3122S (AS-PL)	UD105129S (AS-PL)
UD13167S (AS-PL)	STR54124 (WOODAUTO)
STRS187 (3EFFE)	ANM12324X (ANDEL)
26-5053 (ELSTOCK)	LES0216 (LUCAS)
LRS03889 (LUCAS)	260018 (CQ)
STR0018 (ELECTROLOG)	