



Especificaciones

Especificación	Valor
No./mount. holes [qty.]	3 qty
O.1 [mm]	111 mm
No./mount. holes with thread [qty.]	0 qty
L.1 [mm]	294 mm
Rotation	CW
Size A [mm]	105 mm
Size B [mm]	41 mm
No./teeth	11 qty
No./teeth (fits into) [qty.]	11 qty
Power	4.5 kW
O.3 [mm]	111 mm
O.2 [mm]	136 mm
C.1 [mm]	13.50 mm
Voltage	24 V
C.3 [mm]	13.50 mm
C.2 [mm]	13.50 mm

Aplicaciones

Marca	Vehículo
JOHN	DEERE

Código original

0-24000-3150	0-24000-3151
1-402-25W	19868

Código equivalente (Fabricante del vehículo)

114267 (CARGO)	F032114267 (CARGO)
1811003310 (ISUZU)	1811003380 (ISUZU)
1811003381 (ISUZU)	8983763930 (ISUZU)
185-24011 (ROBERT'S)	19868 (LESTER)
19868N (WAI / TRANSPO)	20446226BN (REAL)
20446226OE (REAL)	246-25227 (DIXIE)
91-28-4069 (WILSON)	CST50622AS (CASCO)
CST50622GS (CASCO)	S9140 (AS-PL)
UD02164S (AS-PL)	S24NK0029A2 (SIDAT)
STK4267 (KRAUF)	254572 (KUHNER)
254572K (KUHNER)	220633 (ERA)
6050622.0 (SANDO)	6050622.1 (SANDO)
131.515.113.170 (PSH)	131.515.113.710 (PSH)
S129.620 (PSH)	S143.994 (PSH)
5150161 (MEAT & DORIA)	STR8819 (ELECTROLOG)