



Especificaciones

Especificación	Valor
No./mount. holes [qty.]	3 qty
O.1 [mm]	90 mm
No./mount. holes with thread [qty.]	0 qty
L.1 [mm]	338 mm
Rotation	CW
Size A [mm]	89 mm
Size B [mm]	46 mm
No./teeth	10 qty
No./teeth (fits into) [qty.]	10 qty
Power	2.8 kW
O.3 [mm]	90 mm
Oil sealed	No
O.2 [mm]	127 mm
C.1 [mm]	10.50 mm
Voltage	12 V
C.3 [mm]	10.50 mm
C.2 [mm]	10.50 mm

Aplicaciones

Marca
PERKINS

Código original

10461446	10461447
RE503093	

Código equivalente (Fabricante del vehículo)

0-23000-1830 (NIKKO)	0-23000-1870 (NIKKO)
0001359029 (BOSCH)	0001359058 (BOSCH)
0001359114 (BOSCH)	0001362302 (BOSCH)
111041 (CARGO)	F032111041 (CARGO)
140-28105 (ROBERT'S)	201-28107 (DIXIE)
254219 (KUHNER)	254219N (KUHNER)
254439 (KUHNER)	254439M (KUHNER)
254439N (KUHNER)	60968 (KUHNER)
60968N (KUHNER)	35258940 (PRESTOLITE)
35259600 (PRESTOLITE)	35259690 (PRESTOLITE)
35261175 (PRESTOLITE)	50-8406 (WAI / TRANSPO)
6318R (WAI / TRANSPO)	6584N (WAI / TRANSPO)
6586N (WAI / TRANSPO)	6854 (LESTER)
8681 (CEVAM)	MAV123500 (SIOM)
MAV621050 (SIOM)	STRW292 (3EFFE)
S1054 (AS-PL)	UD02186S (AS-PL)
UD02188S (AS-PL)	332071 (LOGISTIK)
STR2025 (ELECTROLOG)	STRX734 (ELECTROLOG)
12500790 (PERKINS)	1313394 (HYSTER)
RE503093 (JOHN DEERE)	RE503120 (JOHN DEERE)
RE507236 (JOHN DEERE)	RE509025 (JOHN DEERE)
RE59010 (JOHN DEERE)	STX210090 (STARDAX)