



Especificaciones

Especificación	Valor
No./mount. holes [qty.]	3 qty
O.1 [mm]	127 mm
No./mount. holes with thread [qty.]	0 qty
L.1 [mm]	339 mm
Rotation	CW
Size A [mm]	89 mm
Size B [mm]	46 mm
No./teeth	10 qty
No./teeth (fits into) [qty.]	10 qty
Power	2.8 kW
O.3 [mm]	90 mm
O.2 [mm]	90 mm
C.1 [mm]	11.00 mm
Voltage	12 V
C.3 [mm]	11.00 mm
C.2 [mm]	11.00 mm

Aplicaciones

Marca	Vehículo	Tipos de modelo	Desde	Hasta
BOBCAT	853H	4JB1	01/1991	12/1994
BOBCAT	843HC	4JB1	01/1989	12/1992
BOBCAT	853C	4JB1	01/1994	12/1996
BOBCAT	853HC	4JB1	01/1994	12/1996
BOBCAT	843B	4JB1	01/1990	12/1992
BOBCAT	853	4JB1	01/1990	12/1994

Código original (Fabricante del vehículo)

0-23000-1990	10461460
10461460 (DELCO)	10479604
10479604 (DELCO)	1113285
1113285 (DELCO)	111383
F032111383	20409511BN
20409511OE	254218
60843	60843M
60843N	35258940
50-8429	6578N
6060115	6578
6651210	6651664
CGB-1633	CST60115AS
CST60115GS	MAV621080
MAV621140	STR80147
STRF438	STRL655
STRS629	UD02202S
STR2024	3134772
3675172RX	3924410
3935071	

Código equivalente (Fabricante del vehículo)

0-23000-1990 (NIKKO)	111383 (CARGO)
F032111383 (CARGO)	20409511BN (REAL)
20409511OE (REAL)	254218 (KUHNER)
60843 (KUHNER)	60843M (KUHNER)
60843N (KUHNER)	35258940 (PRESTOLITE)
50-8429 (WAI / TRANSPO)	6578N (WAI / TRANSPO)
6060115 (SANDO)	6578 (LESTER)
6651210 (MANDO)	6651664 (MANDO)
CGB-1633 (AINDE)	CST60115AS (CASCO)
CST60115GS (CASCO)	MAV621080 (SIOM)
MAV621140 (SIOM)	STR80147 (WOODAUTO)
STRF438 (3EFFE)	STRL655 (3EFFE)
STRS629 (3EFFE)	UD02202S (AS-PL)
STR2024 (ELECTROLOG)	3134772 (VOLVO)
3675172RX (CUMMINS)	3924410 (CUMMINS)
3935071 (CUMMINS)	