



Especificaciones

Especificación	Valor
No./mount. holes [qty.]	2 qty
O.1 [mm]	105 mm
No./mount. holes with thread [qty.]	0 qty
L.1 [mm]	339 mm
Rotation	CW
Size A [mm]	82 mm
Size B [mm]	34 mm
No./teeth	10 qty
No./teeth (fits into) [qty.]	10 qty
Power	2.5 kW
C.1 [mm]	12.50 mm
Voltage	12 V
C.2 [mm]	12.50 mm

Aplicaciones

Marca	Vehículo	Tipos de modelo	Desde	Hasta
CLARK	Various Mod-els		01/1968	
BOBCAT	975			
BOBCAT	T 770 3.8	V3800-DI-TE3		
JOHN DEERE	Series 2050 2550		01/1983	12/1986
JOHN DEERE	Series 5000 5300	3029DF150	01/1996	12/2000
JOHN DEERE	Series 5000 5500	4039TAT01	01/1996	12/2000

Código original (Fabricante del vehículo)

0-23000-2060	1107577
1107577 (DELCO)	1107599
1107599 (DELCO)	1107863
1107863 (DELCO)	1107871
1107871 (DELCO)	1109251
1109251 (DELCO)	1113271
1113271 (DELCO)	93512
93512 (DELCO)	111221
F032111221	254203
254203N	35259580
50-8422	6570N
6577N	6570
8537	CGB-1574
M100R2017SE	MAV3400
RE509658	RE62916
SE501400	STR80116
S1066	UD02207S
220856	STR2677
STX200819	

Código equivalente (Fabricante del vehículo)

0-23000-2060 (NIKKO)	111221 (CARGO)
F032111221 (CARGO)	254203 (KUHNER)
254203N (KUHNER)	35259580 (LEECE NEVILLE)
50-8422 (WAI / TRANSP0)	6570N (WAI / TRANSP0)
6577N (WAI / TRANSP0)	6570 (LESTER)
8537 (CEVAM)	CGB-1574 (AINDE)
M100R2017SE (PRESTOLITE)	MAV3400 (SIOM)
RE509658 (JOHN DEERE)	RE62916 (JOHN DEERE)
SE501400 (JOHN DEERE)	STR80116 (WOODAUTO)
S1066 (AS-PL)	UD02207S (AS-PL)
220856 (ERA)	STR2677 (ELECTROLOG)
STX200819 (STARDAX)	