



Especificaciones

Especificación	Valor
No./teeth	10 qty
Power	3.2 kW
No./mount. holes [qty.]	2 qty
O.1 [mm]	105 mm
No./mount. holes with thread [qty.]	0 qty
C.1 [mm]	10.50 mm
L.1 [mm]	272 mm
Voltage	12 V
Rotation	CW
C.2 [mm]	10.50 mm
Size A [mm]	82 mm
Size B [mm]	35 mm

Aplicaciones

Marca	Vehículo
JOHN	DEERE

Código original

AZF4655[	IS1027
RE19196	

Código equivalente (Fabricante del vehículo)

273-32104 (DIXIE)	TS-6265 (DIXIE)
6040246 (SANDO)	630.505.102 (PSH)
630.537.102 (PSH)	630.537.102.030 (PSH)
630.537.102.500 (PSH)	630.538.102 (PSH)
630.538.102.460 (PSH)	S134.180 (PSH)
S134.181 (PSH)	S144.176 (PSH)
S144.177 (PSH)	72735921 (MAHLE)
MS 293 (MAHLE)	MS293A (MAHLE)
AJ59342 (JOHN DEERE)	RE19196 (JOHN DEERE)
RE19275 (JOHN DEERE)	RE41799 (JOHN DEERE)
RE42730 (JOHN DEERE)	RE49033 (JOHN DEERE)
RE501693 (JOHN DEERE)	RE505746 (JOHN DEERE)
RE509658 (JOHN DEERE)	RE516157 (JOHN DEERE)
RE51694 (JOHN DEERE)	RE529594 (JOHN DEERE)
RE533976 (JOHN DEERE)	RE54092 (JOHN DEERE)
RE551445 (JOHN DEERE)	RE59590 (JOHN DEERE)
RE62916 (JOHN DEERE)	RE68470 (JOHN DEERE)
SE501400 (JOHN DEERE)	SE501402 (JOHN DEERE)
SE501425 (JOHN DEERE)	SE501428 (JOHN DEERE)
SE501852 (JOHN DEERE)	TY24305 (JOHN DEERE)
TY24438 (JOHN DEERE)	TY25971 (JOHN DEERE)
TY34438 (JOHN DEERE)	TY6688 (JOHN DEERE)
TY6719 (JOHN DEERE)	CST40246 (CASCO)
CST40246AS (CASCO)	CST40246ES (CASCO)
CST40246GS (CASCO)	CST40246OS (CASCO)
CST40246RS (CASCO)	DRS0303 (DELCO)
MAHMS293 (WOODAUTO)	MAV123600 (SIOM)
MAV172060 (SIOM)	MAV421720 (SIOM)
MAV422460 (SIOM)	STI4603 (KRAUF)
S9325S (AS-PL)	UD105194S (AS-PL)
UD14889S (AS-PL)	S12ML0709 (SIDAT)
S12ML0709A2 (SIDAT)	ANM12523X (ANDEL)
STR79146 (ELECTROLOG)	STR7958 (ELECTROLOG)
STX200520 (STARDAX)	STX200520R (STARDAX)
STX200819 (STARDAX)	