



Especificaciones

Especificación	Valor
No./mount. holes [qty.]	3 qty
O.1 [mm]	127 mm
No./mount. holes with thread [qty.]	0 qty
L.1 [mm]	348 mm
Rotation	CW
Size A [mm]	89 mm
Size B [mm]	29 mm
No./teeth	10 qty
Power	4.2 kW
O.3 [mm]	90 mm
O.2 [mm]	90 mm
C.1 [mm]	11.00 mm
Voltage	12 V
C.3 [mm]	11.00 mm
C.2 [mm]	11.00 mm

Aplicaciones

Marca
PERKINS

Código original

16058	3317010
AZF4318	

Código equivalente (Fabricante del vehículo)

16058N (WAI / TRANSPO)	182-30448 (ROBERT'S)
20419512OE (REAL)	254891 (KUHNER)
254891M (KUHNER)	273-42108 (DIXIE)
TS-6269 (DIXIE)	3317010 (PERKINS)
T406154 (PERKINS)	6021215.1 (SANDO)
7169479 (BOBCAT)	7220938 (BOBCAT)
72735854 (MAHLE)	MS 226 (MAHLE)
8013 (CEVAM)	CST21215GS (CASCO)
S9362S (AS-PL)	UD16540S (AS-PL)
700.531.103.310 (PSH)	S145.086 (PSH)
STR79355 (ELECTROLOG)	STR79356 (ELECTROLOG)