



Especificaciones

Especificación	Valor
No./mount. holes [qty.]	3 qty
O.1 [mm]	127 mm
No./mount. holes with thread [qty.]	0 qty
L.1 [mm]	322 mm
Rotation	CW
Size A [mm]	89 mm
Size B [mm]	48 mm
No./teeth	10 qty
Power	4.2 kW
O.3 [mm]	90 mm
O.2 [mm]	90 mm
C.1 [mm]	11.50 mm
Voltage	12 V
C.3 [mm]	11.50 mm
C.2 [mm]	11.50 mm

Aplicaciones

Marca	Vehículo	Tipos de modelo	Desde	Hasta
JOHN DEERE	Series 6 6140R	6068HL490		
JOHN DEERE	Series 6 6155M, 6155R			
JOHN DEERE	Series 6010 6410, 6510		01/1997	12/2001
JOHN DEERE	Series 6020 6520		01/2002	12/2007
JOHN DEERE	Series 6010 6610		01/1997	12/2003
JOHN DEERE	Series 6020 6620		01/2002	12/2007
JOHN DEERE	Series 6010 6810		01/1997	12/2003
JOHN DEERE	Series 6020 6820		01/2002	12/2007
JOHN DEERE	Series 6010 6910		01/1999	12/2003
JOHN DEERE	Series 6020 6920, 6820 S		01/2002	12/2007

Código original (Fabricante del vehículo)

11.131.237	11.131.237 (ISKRA / LETRIKA)
AZF4570	AZF4570 (ISKRA / LETRIKA)
IS1157	IS1157 (ISKRA / LETRIKA)
182-30324	25-5061
6632415	72736044
MS 416	8263
AL70852	AL81154
RE503226	RE504807
SE501855	CGB-20002
CGB-23818	LRS03898
LRS3898	MAHMS416
MAV122280	SG2000
S9274	UD13181S
STR7818	STX200383
STX200904	STX201006
STX201072	

Código equivalente (Fabricante del vehículo)

182-30324 (ROBERT'S)	25-5061 (ELSTOCK)
6632415 (BOBCAT)	72736044 (MAHLE)
MS 416 (MAHLE)	8263 (CEVAM)
AL70852 (JOHN DEERE)	AL81154 (JOHN DEERE)
RE503226 (JOHN DEERE)	RE504807 (JOHN DEERE)
SE501855 (JOHN DEERE)	CGB-20002 (AINDE)
CGB-23818 (AINDE)	LRS03898 (LUCAS)
LRS3898 (LUCAS)	MAHMS416 (WOODAUTO)
MAV122280 (SIOM)	SG2000 (GHIBAUDI)
S9274 (AS-PL)	UD13181S (AS-PL)
STR7818 (ELECTROLOG)	STX200383 (STARDAX)
STX200904 (STARDAX)	STX201006 (STARDAX)
STX201072 (STARDAX)	