



Especificaciones

Especificación	Valor
No./mount. holes [qty.]	3 qty
O.1 [mm]	90 mm
No./mount. holes with thread [qty.]	0 qty
L.1 [mm]	351 mm
Rotation	CW
Size A [mm]	88.5 mm
Size B [mm]	29.5 mm
No./teeth	10 qty
Power	4.2 kW
O.3 [mm]	127 mm
Insulated return	Yes
O.2 [mm]	90 mm
C.1 [mm]	11.00 mm
Voltage	12 V
C.3 [mm]	11.00 mm
C.2 [mm]	11.00 mm

Aplicaciones

Marca
CATERPILLAR

Código original

3704009	AZF4103
IS1129	

Código equivalente (Fabricante del vehículo)

UD21477S (AS-PL)	256041M (KUHNER)
640.551.103.090 (PSH)	640.551.103.311 (PSH)
S143.441 (PSH)	S144.488 (PSH)
CST21246AS (CASCO)	CST21246GS (CASCO)
109472 (FARCOM)	72735747 (MAHLE)
MS119 (MAHLE)	N37636 (PERKINS)
3704009 (CATERPILLAR)	N40982 (CATERPILLAR)
WG2044878 (WILMINK GROUP)	20419642BN (REAL)
20419642OE (REAL)	6021246.0 (SANDO)
6021246.1 (SANDO)	LETIS1129 (WOODAUTO)
MAHMS119 (WOODAUTO)	STR60651 (WOODAUTO)
182-30506 (ROBERT'S)	UNIT BOM 182-1150 (WAI / TRANSP0)