



Especificaciones

Especificación	Valor
No./mount. holes [qty.]	4 qty
O.1 [mm]	124 mm
No./mount. holes with thread [qty.]	1 qty
L.1 [mm]	322 mm
Rotation	CW
Size A [mm]	89 mm
Size B [mm]	47 mm
No./teeth	10 qty
No./teeth (fits into) [qty.]	10 qty
C.4 [mm]	11.00 mm
Power	4.2 kW
O.4 [mm]	90 mm
O.3 [mm]	90 mm
O.2 [mm]	30.5 mm
C.1 [mm]	11.00 mm
Voltage	12 V
C.3 [mm]	11.00 mm
C.2 [mm]	M12x1.75 mm

Aplicaciones

Marca	Vehículo
JOHN	DEERE

Código original

AZF4597	IS1063
RE105298	

Código equivalente (Fabricante del vehículo)

0001362324 (BOSCH)	10-14194S (WHITE)
30-3123383 (WHITE)	10461450 (DELCO)
10461451 (DELCO)	10465049 (DELCO)
10465050 (DELCO)	1107866 (DELCO)
1109198 (DELCO)	1109263 (DELCO)
1113281 (DELCO)	1113282 (DELCO)
12301341 (DELCO)	1998330 (DELCO)
323-674 (DELCO)	323-684 (DELCO)
323442 (DELCO)	323443 (DELCO)
113454 (CARGO)	F032113454 (CARGO)
18195 (LESTER)	4274 (LESTER)
182-30104 (ROBERT'S)	18483N (WAI / TRANSPO)
1903103M91 (MASSEY FERGUSON)	1903117M91 (MASSEY FERGUSON)
517533M93 (MASSEY FERGUSON)	579937M91 (MASSEY FERGUSON)
228000-6400 (DENSO)	254669 (KUHNER)
260-23120 (DIXIE)	3185C37G01 (THERMO KING)
347198 (MERCURY)	646218 (MERCURY)
35259630 (PRESTOLITE)	S5011L (PRESTOLITE)
450732R91 (CASE)	596493R92 (CASE)
6010343.0 (SANDO)	6651258 (BOBCAT)
6651664 (BOBCAT)	91-01-4310 (WILSON)
91-23-6508 (WILSON)	910886 (CLARK)
CGB-1633 (AINDE)	CGB-23818 (AINDE)
CST10343AS (CASCO)	LETIS1063 (WOODAUTO)
STR60621 (WOODAUTO)	MAV122280 (SIOM)
MAV123430 (SIOM)	MS 94 (MAHLE)
MS94A (MAHLE)	RE105298 (JOHN DEERE)
RE501766 (JOHN DEERE)	RE501767 (JOHN DEERE)
RE505744 (JOHN DEERE)	RE507639 (JOHN DEERE)
RE508322 (JOHN DEERE)	RE509903 (JOHN DEERE)
RE540136 (JOHN DEERE)	RE60171 (JOHN DEERE)
RE60239 (JOHN DEERE)	RE70728 (JOHN DEERE)
SE501850 (JOHN DEERE)	SE502631 (JOHN DEERE)
STRF223 (3EFFE)	STRS640 (3EFFE)
S9070 (AS-PL)	UD11315S (AS-PL)
332072 (LOGISTIK)	STR7930 (ELECTROLOG)
STX200383 (STARDAX)	STX200904 (STARDAX)
STX201006 (STARDAX)	STX201072 (STARDAX)