



Especificaciones

Especificación	Valor
No./mount. holes [qty.]	3 qty
O.1 [mm]	88 mm
No./mount. holes with thread [qty.]	0 qty
L.1 [mm]	348 mm
Rotation	CW
Size A [mm]	89 mm
Size B [mm]	29.5 mm
No./teeth	10 qty
Power	4.2 kW
O.3 [mm]	88 mm
O.2 [mm]	128 mm
C.1 [mm]	11.00 mm
Voltage	12 V
C.3 [mm]	11.00 mm
C.2 [mm]	11.00 mm

Aplicaciones

Marca
PERKINS

Código original

2873K607	33408
AZF4270	

Código equivalente (Fabricante del vehículo)

116136 (CARGO)	F032116136 (CARGO)
182-30169 (ROBERT'S)	204199410E (REAL)
273-42115 (DIXIE)	2873K607 (PERKINS)
2873K608 (PERKINS)	2873K612 (PERKINS)
33408N (WAI / TRANSPO)	6021149 (SANDO)
CST21149 (CASCO)	CST21149AS (CASCO)
CST21149ES (CASCO)	CST21149GS (CASCO)
CST21149OS (CASCO)	CST21149RS (CASCO)
LETIS1194 (WOODAUTO)	MAHMS401 (WOODAUTO)
STR60647 (WOODAUTO)	MS 401 (MAHLE)
S9234 (AS-PL)	UD11319S (AS-PL)
332259 (LOGISTIK)	STR79223 (ELECTROLOG)
STR79224 (ELECTROLOG)	STR79225 (ELECTROLOG)