



Especificaciones

Especificación	Valor
No./mount. holes [qty.]	3 qty
O.1 [mm]	128 mm
No./mount. holes with thread [qty.]	0 qty
L.1 [mm]	350 mm
Rotation	CW
Size A [mm]	89 mm
Size B [mm]	29 mm
No./teeth	10 qty
Power	4.2 kW
O.3 [mm]	90 mm
O.2 [mm]	90 mm
C.1 [mm]	10.50 mm
Voltage	12 V
C.3 [mm]	10.50 mm
C.2 [mm]	10.50 mm

Aplicaciones

Marca
PERKINS

Código original

2873A031	30326
AZF4248	

Código equivalente (Fabricante del vehículo)

114852 (CARGO)	F032114852 (CARGO)
182-30175 (ROBERT'S)	20419551OE (REAL)
25-4223 (ELSTOCK)	26925193A (PERKINS)
2873A031 (PERKINS)	2873K604 (PERKINS)
2873K605 (PERKINS)	2873K606 (PERKINS)
2873K635 (PERKINS)	3317010 (PERKINS)
6021155.1 (SANDO)	72736031 (MAHLE)
MS403 (MAHLE)	CST21155GS (CASCO)
DRS0277 (DELCO)	LETIS1202 (WOODAUTO)
MAHMS403 (WOODAUTO)	STR60650 (WOODAUTO)
LRS02551 (LUCAS)	LRS2551 (LUCAS)
MAV231550 (SIOM)	PRSL275 (3EFFE)
STRL275L (3EFFE)	S9235 (AS-PL)
UD11320S (AS-PL)	TS-6282 (DIXIE)
S12ML0292A2 (SIDAT)	ANM12497X (ANDEL)
STR79259 (ELECTROLOG)	30326N (WAI / TRANSPO)
7169479 (BOBCAT)	7220938 (BOBCAT)
STX200560 (STARDAX)	STX200678 (STARDAX)
STX210091 (STARDAX)	