



Especificaciones

Especificación	Valor
No./teeth	10 qty
Power	4 kW
No./mount. holes [qty.]	2 qty
O.1 [mm]	105 mm
No./mount. holes with thread [qty.]	0 qty
C.1 [mm]	13.50 mm
L.1 [mm]	322 mm
Voltage	24 V
Rotation	CW
C.2 [mm]	13.50 mm
Size A [mm]	82.5 mm
Size B [mm]	35 mm

Aplicaciones

Marca	Vehículo
JOHN	DEERE

Código original

6596	AZJ3326
IS1088	RE503118

Código equivalente (Fabricante del vehículo)

0-23000-2050 (NIKKO)	02-23-1041 (NIKKO)
0001368059 (BOSCH)	10461444 (DELCO)
1113272 (DELCO)	1998519 (DELCO)
120-30364 (ROBERT'S)	255200 (KUHNER)
260-67225 (DIXIE)	35259650 (PRESTOLITE)
S5007L (PRESTOLITE)	6010708 (SANDO)
631.001.102 (PSH)	631.504.102 (PSH)
S134.289 (PSH)	S134.356 (PSH)
S144.328 (PSH)	6596N (WAI / TRANSPO)
8477 (CEVAM)	91-01-4377 (WILSON)
CST10708 (CASCO)	CST10708AS (CASCO)
CST10708ES (CASCO)	CST10708GS (CASCO)
CST10708OS (CASCO)	CST10708RS (CASCO)
MAHMS96 (WOODAUTO)	STR20034 (WOODAUTO)
MAV123600 (SIOM)	MAV127080 (SIOM)
MS 96 (MAHLE)	RE503118 (JOHN DEERE)
RE51725 (JOHN DEERE)	RE52120 (JOHN DEERE)
RE52150 (JOHN DEERE)	RE522738 (JOHN DEERE)
RE525799 (JOHN DEERE)	RE67086 (JOHN DEERE)
SE502286 (JOHN DEERE)	TY24303 (JOHN DEERE)
STRJ314 (3EFFE)	STRJ675 (3EFFE)
STRL842 (3EFFE)	UD13626S (AS-PL)
STR10314 (ELECTROLOG)	