



Especificaciones

Especificación	Valor
No./mount. holes [qty.]	3 qty
O.1 [mm]	146 mm
No./mount. holes with thread [qty.]	0 qty
L.1 [mm]	316 mm
Rotation	CW
Size A [mm]	121 mm
Size B [mm]	48 mm
No./teeth	11 qty
No./teeth (fits into) [qty.]	11 qty
Power	6 kW
O.3 [mm]	96 mm
O.2 [mm]	156 mm
C.1 [mm]	16.00 mm
Voltage	24 V
C.3 [mm]	16.00 mm
C.2 [mm]	16.00 mm

Aplicaciones

Marca
HINO

Código original

0365-602-0011	1-639-25W
19102	28100-2862

Código equivalente (Fabricante del vehículo)

STRF474 (3EFFE)	S9135 (AS-PL)
UD02178S (AS-PL)	CST37604AS (CASCO)
8065 (CEVAM)	19085300 (DELCO)
STR9810 (ELECTROLOG)	8880803 (FRIESEN)
28100-2862 (HINO)	28100-2862A (HINO)
28100-2863 (HINO)	28100-2863A (HINO)
28100-2864A (HINO)	28100-2865 (HINO)
28100-2865A (HINO)	28100-2865C (HINO)
28100-E0334 (HINO)	28100-E0640 (HINO)
STW3862 (KRAUF)	261.513.113.170 (PSH)
261.513.113.200 (PSH)	261.513.113.440 (PSH)
261.513.113.540 (PSH)	S132.064 (PSH)
S144.830 (PSH)	20444406BN (REAL)
186-35067N (ROBERT'S)	6037604.0 (SANDO)
MAV396040A (SIOM)	19102N (WAI / TRANSP0)
STR75606 (WOODAUTO)	WOOSTR75606 (WOODAUTO)