



Specifications

Specification	Value
E.2 [mm]	57.5 mm
E.3 [mm]	61 mm
O.D.1 [mm]	52 mm
Plug	PL_2804
D.3 [mm]	11.00 mm
L.1 [mm]	184.5 mm
E.1 [mm]	60 mm
Size A [mm]	56 mm
Size C [mm]	50 mm
D.1 [mm]	10.50 mm
D.2 [mm]	9.50 mm
Voltage	12 V
Amp	160 A
Pulley	AFP
G [qty.]	6 qty

Applications

Make
CHRYSLER

Original Code

04801779AG	11572
421000-0750	

Equivalent Code (Vehicle Manufacturer)

ALTJ367 (3EFFE)	UD15376A (AS-PL)
0986CR6192 (BOSCH)	CAL40511AS (CASCO)
04801779AG (CHRYSLER)	4801779AG (CHRYSLER)
4801779AH (CHRYSLER)	56029624AA (CHRYSLER)
56029624AB (CHRYSLER)	P04801779AG (CHRYSLER)
RL801779AG (CHRYSLER)	A-80639 (DIXIE)
A-80693 (DIXIE)	56029580AA (DODGE)
56029580AB (DODGE)	56029580AC (DODGE)
K04801779AI (DODGE)	K56029624AC (DODGE)
ALT6591 (ELECTROLOG)	27-7807 (ELSTOCK)
ALM3587 (KRAUF)	554820RI (KUHNER)
LRA04198 (LUCAS)	LRA4198 (LUCAS)
A002TX3481 (MITSUBISHI)	A002TX3481ZC (MITSUBISHI)
A002TX3581 (MITSUBISHI)	A002TX3581ZC (MITSUBISHI)
A002TX3581ZE (MITSUBISHI)	A2TX3481 (MITSUBISHI)
A2TX3481ZC (MITSUBISHI)	A2TX3581 (MITSUBISHI)
A2TX3581ZC (MITSUBISHI)	A2TX3581ZE (MITSUBISHI)
89216463 (POWERMAX)	20132115BN (REAL)
230-20146 (ROBERT'S)	2040511.0 (SANDO)
11554N (WAI / TRANSP0)	11687 (WAI / TRANSP0)
11687N (WAI / TRANSP0)	11687R (WAI / TRANSP0)
90-27-3455 (WILSON)	90-27-3455N (WILSON)
90-27-3456 (WILSON)	