



Specifications

| Specification | Value    |
|---------------|----------|
| E.2 [ mm ]    | 98.5 mm  |
| E.3 [ mm ]    | 92 mm    |
| O.D.1 [ mm ]  | 57 mm    |
| Plug          | PL_4000  |
| D.3 [ mm ]    | 13.00 mm |
| D.4 [ mm ]    | 13.00 mm |
| L.1 [ mm ]    | 171.5 mm |
| E.4 [ mm ]    | 18 mm    |
| E.1 [ mm ]    | 45 mm    |
| Size A [ mm ] | 29 mm    |
| Size C [ mm ] | 68 mm    |
| D.1 [ mm ]    | 11.00 mm |
| D.2 [ mm ]    | 10.50 mm |
| Voltage       | 12 V     |
| Amp           | 180 A    |
| Pulley        | AP       |
| G [ qty. ]    | 8 qty    |

Applications

| Make |
|------|
| FORD |

Original Code

|             |             |
|-------------|-------------|
| 104210-6180 | 104210-6181 |
| 11534       | 9C2T10300CA |

Equivalent Code (Vehicle Manufacturer)

|                        |                       |
|------------------------|-----------------------|
| 11405R (WAI / TRANSP0) | 12898 (DELCO)         |
| 195.996.180 (PSH)      | A131.472 (PSH)        |
| A148.310 (PSH)         | 20132174OE (REAL)     |
| 2040471 (SANDO)        | 27060-38050 (TOYOTA)  |
| 554582RID (KUHNER)     | 90-29-5728 (WILSON)   |
| A-80393 (DIXIE)        | ALTE962 (3EFFE)       |
| CAL40471GS (CASCO)     | DENDAN1208 (WOODAUTO) |
| UD11399A (AS-PL)       | UD11510A (AS-PL)      |
| ALT6481 (ELECTROLOG)   |                       |