

Specifications

| Specification                         | Value    |
|---------------------------------------|----------|
| No./mount. holes [ qty. ]             | 3 qty    |
| O.1 [ mm ]                            | 104 mm   |
| No./mount. holes with thread [ qty. ] | 0 qty    |
| L.1 [ mm ]                            | 252 mm   |
| Rotation                              | CW       |
| Size A [ mm ]                         | 110 mm   |
| Size B [ mm ]                         | 27 mm    |
| No./teeth                             | 9 qty    |
| No./teeth (fits into) [ qty. ]        | 9 qty    |
| Power                                 | 2.3 kW   |
| O.3 [ mm ]                            | 147 mm   |
| O.2 [ mm ]                            | 104 mm   |
| C.1 [ mm ]                            | 12.00 mm |
| Voltage                               | 12 V     |
| C.3 [ mm ]                            | 12.00 mm |
| C.2 [ mm ]                            | 12.00 mm |

Applications

| Make |
|------|
| FORD |

Original Code

|            |             |
|------------|-------------|
| 0001223010 | 2C3511001AA |
|------------|-------------|

Equivalent Code (Vehicle Manufacturer)

|                     |                       |
|---------------------|-----------------------|
| 254878 (KUHNER)     | 2C3511001AA (FORD)    |
| XC3U11000BA (FORD)  | 35259890 (PRESTOLITE) |
| STR50584 (WOODAUTO) | STRL764 (3EFFE)       |
| S0320 (AS-PL)       | STR1669 (ELECTROLOG)  |