



Specifications

Specification	Value
No./mount. holes [qty.]	3 qty
O.1 [mm]	90 mm
No./mount. holes with thread [qty.]	0 qty
L.1 [mm]	315 mm
Rotation	CW
Size A [mm]	89 mm
Size B [mm]	48 mm
No./teeth	10 qty
No./teeth (fits into) [qty.]	10 qty
Power	3 kW
O.3 [mm]	90 mm
O.2 [mm]	127 mm
C.1 [mm]	11.00 mm
Voltage	12 V
C.3 [mm]	11.00 mm
C.2 [mm]	11.00 mm

Applications

Make	Vehicle
JOHN	DEERE

Original Code

0001230008	120-6109
RE501551	

Equivalent Code (Vehicle Manufacturer)

CST10381AS (CASCO)	CST10381GS (CASCO)
88215000 (POWERMAX)	RE501551 (JOHN DEERE)
RE507943 (JOHN DEERE)	RE509856 (JOHN DEERE)
254366 (KUHNER)	630.505.103.010 (PSH)
S134.453 (PSH)	STR50416 (WOODAUTO)
DRS0362 (DELCO)	6010381.0 (SANDO)
6010381.1 (SANDO)	20401183BN (REAL)
20401183OE (REAL)	114195 (CARGO)
F032114195 (CARGO)	STRS677 (3EFFE)
331300 (LOGISTIK)	120-6109 (WAI / TRANSPO)
CGB-93008 (AINDE)	S12BH0704A2 (SIDAT)
S0296 (AS-PL)	5010530 (MEAT & DORIA)
STR10005 (ELECTROLOG)	