



Specifications

Specification	Value
No./mount. holes [qty.]	2 qty
O.1 [mm]	91 mm
No./mount. holes with thread [qty.]	1 qty
L.1 [mm]	213 mm
Rotation	CW
Size A [mm]	70 mm
Size B [mm]	33 mm
No./teeth	9 qty
No./teeth (fits into) [qty.]	9 qty
Power	1 kW
C.1 [mm]	M12x1.25 mm
Voltage	12 V
C.2 [mm]	11.00 mm

Applications

Make
HONDA

Original Code

17998	31200-R3R-E01
428000-3390	428000-5410

Equivalent Code (Vehicle Manufacturer)

S6215S (AS-PL)	UD12043S (AS-PL)
UD20503S (AS-PL)	336596 (LOGISTIK)
CGB-20673 (AINDE)	CGB-54441 (AINDE)
AEY2768 (AUTOELECTRO)	116256 (CARGO)
F032116256 (CARGO)	CST40417AS (CASCO)
CST40417GS (CASCO)	3359 (CEVAM)
DRS0673 (DELCO)	RAS31784 (DELCO)
246-08103 (DIXIE)	S-80495 (DIXIE)
25-4441 (ELSTOCK)	220998A (ERA)
J5214060 (HERTH+BUSS)	31200-PWA-901 (HONDA)
31200-R3R-E01 (HONDA)	31200-RB1-003 (HONDA)
31200-RB1-013 (HONDA)	DSKEF (HONDA)
DSKEW (HONDA)	STN3102 (KRAUF)
255315 (KUHNER)	255315R (KUHNER)
LRS02768 (LUCAS)	LRS2768 (LUCAS)
88214662 (POWERMAX)	120.577.092.050 (PSH)
120.577.092.058 (PSH)	120.577.092.059 (PSH)
120.577.092.261 (PSH)	S129.630 (PSH)
S144.020 (PSH)	20432714BN (REAL)
20432714OE (REAL)	6040417.0 (SANDO)
6040417.1 (SANDO)	MAV424170 (SIOM)
MAV424170A (SIOM)	458943 (VALEO)
17998N (WAI / TRANSP0)	19013N (WAI / TRANSP0)
91-29-5794 (WILSON)	91-29-5794N (WILSON)
DENDSN1385 (WOODAUTO)	WOOSTR70418 (WOODAUTO)
STR6731 (ELECTROLOG)	