



Specifications

Specification	Value
No./teeth	10 qty
Power	1.4 kW
No./mount. holes [qty.]	2 qty
O.1 [mm]	99 mm
No./mount. holes with thread [qty.]	0 qty
C.1 [mm]	11.50 mm
L.1 [mm]	221 mm
Voltage	12 V
Rotation	CW
C.2 [mm]	15.50 mm
Size A [mm]	71 mm
Size B [mm]	23 mm

Applications

Make
CHRYSLER

Original Code

128000-4960	128000-5270
17084	2095150

Equivalent Code (Vehicle Manufacturer)

111764 (CARGO)	113100 (CARGO)
F032111764 (CARGO)	F032113100 (CARGO)
17010 (DELCO)	19011800 (DELCO)
17084N (WAI / TRANSP0)	17084R (WAI / TRANSP0)
17466N (WAI / TRANSP0)	17466R (WAI / TRANSP0)
2-1398ND (WAI / TRANSP0)	1877560 (CHRYSLER)
2095150 (CHRYSLER)	2098500 (CHRYSLER)
2785560 (CHRYSLER)	2875560 (CHRYSLER)
3255250 (CHRYSLER)	3656575 (CHRYSLER)
3656650 (CHRYSLER)	3675560 (CHRYSLER)
3755250 (CHRYSLER)	3755259 (CHRYSLER)
3755900 (CHRYSLER)	4091950 (CHRYSLER)
4091975 (CHRYSLER)	4106113 (CHRYSLER)
4106114 (CHRYSLER)	4111855 (CHRYSLER)
4111860 (CHRYSLER)	4145300 (CHRYSLER)
4145359 (CHRYSLER)	4145360 (CHRYSLER)
4145568 (CHRYSLER)	4349144 (CHRYSLER)
4379143 (CHRYSLER)	4379160 (CHRYSLER)
5226844 (CHRYSLER)	53005984 (CHRYSLER)
20432991BN (REAL)	246-14132 (DIXIE)
S-8215 (DIXIE)	25-2278 (ELSTOCK)
255010 (KUHNER)	6040199 (SANDO)
830.557.102 (PSH)	830.557.102.461 (PSH)
830.558.102 (PSH)	830.558.102.050 (PSH)
830.558.102.460 (PSH)	S135.443 (PSH)
S135.444 (PSH)	91-29-5079 (WILSON)
CST40199 (CASCO)	CST40199AS (CASCO)
CST40199ES (CASCO)	CST40199GS (CASCO)
CST40199OS (CASCO)	CST40199RS (CASCO)
LRS01396 (LUCAS)	LRS1396 (LUCAS)
MAV421990 (SIOM)	MD017649 (MITSUBISHI)
S6150 (AS-PL)	UD12359S (AS-PL)
STR70237 (WOODAUTO)	STRE110 (3EFFE)
STRF427 (3EFFE)	S12DE0750A2 (SIDAT)
336556 (LOGISTIK)	STR6582 (ELECTROLOG)
STR6583 (ELECTROLOG)	STX200375 (STARDAX)
STX201171 (STARDAX)	