



Specifications

Specification	Value
No./teeth	13 qty
Power	1.4 kW
No./mount. holes [qty.]	2 qty
O.1 [mm]	110 mm
No./mount. holes with thread [qty.]	0 qty
C.1 [mm]	9.50 mm
L.1 [mm]	188 mm
Voltage	12 V
Rotation	CW
C.2 [mm]	9.50 mm
Size A [mm]	66 mm
Size B [mm]	18 mm

Applications

Make
SCHAFFER

Original Code

16235-63010	228000-7610
2280006320	

Equivalent Code (Vehicle Manufacturer)

PRSL252 (3EFFE)	STRL252 (3EFFE)
S6277S (AS-PL)	UD14892S (AS-PL)
CST40185AS (CASCO)	CST40185GS (CASCO)
246-15101 (DIXIE)	S-80078 (DIXIE)
25-3480 (ELSTOCK)	16235-63010 (KUBOTA)
16235-63011 (KUBOTA)	16235-63012 (KUBOTA)
17423-63012 (KUBOTA)	7770002602 (KUBOTA)
K756161810 (KUBOTA)	K756161811 (KUBOTA)
K757196800 (KUBOTA)	K757196810 (KUBOTA)
K771161800 (KUBOTA)	K7711968000 (KUBOTA)
254151 (KUHNER)	254151D (KUHNER)
LRS02308 (LUCAS)	LRS2308 (LUCAS)
690.520.132.051 (PSH)	690.520.132.058 (PSH)
690.520.132.260 (PSH)	S134.987 (PSH)
S144.708 (PSH)	20432581BN (REAL)
20432581OE (REAL)	6040185.0 (SANDO)
6040185.1 (SANDO)	MAV421850 (SIOM)
STR30058 (WOODAUTO)	F042S00183 (UNIPOINT)
F042000183 (BOSCH)	STR6112 (ELECTROLOG)
112547 (CARGO)	116630 (CARGO)
F032112547 (CARGO)	F032116630 (CARGO)