



Specifications

| Specification                         | Value      |
|---------------------------------------|------------|
| No./mount. holes [ qty. ]             | 2 qty      |
| O.1 [ mm ]                            | 117 mm     |
| No./mount. holes with thread [ qty. ] | 1 qty      |
| L.1 [ mm ]                            | 189 mm     |
| Rotation                              | CW         |
| Size A [ mm ]                         | 50 mm      |
| Size B [ mm ]                         | 4.5 mm     |
| No./teeth                             | 13 qty     |
| No./teeth (fits into) [ qty. ]        | 13 qty     |
| Power                                 | 1.4 kW     |
| C.1 [ mm ]                            | M10x1.5 mm |
| Voltage                               | 12 V       |
| C.2 [ mm ]                            | 11.50 mm   |

Applications

| Make  |
|-------|
| DODGE |

Original Code

|            |             |
|------------|-------------|
| 17884      | 428000-2050 |
| 56029750AA |             |

Equivalent Code (Vehicle Manufacturer)

|                        |                       |
|------------------------|-----------------------|
| 17884N (WAI / TRANSP0) | 56029750AA (CHRYSLER) |
| 91-29-5641 (WILSON)    | S-80389 (DIXIE)       |
| S6100 (AS-PL)          | UD00740S (AS-PL)      |
| STN4051 (KRAUF)        |                       |