



Specifications

| Specification                         | Value       |
|---------------------------------------|-------------|
| No./teeth                             | 9 qty       |
| Power                                 | 2 kW        |
| No./mount. holes [ qty. ]             | 2 qty       |
| O.1 [ mm ]                            | 91 mm       |
| No./mount. holes with thread [ qty. ] | 2 qty       |
| C.1 [ mm ]                            | M10x1.25 mm |
| L.1 [ mm ]                            | 229 mm      |
| Voltage                               | 12 V        |
| Rotation                              | CW          |
| C.2 [ mm ]                            | M10x1.25 mm |
| Size A [ mm ]                         | 74 mm       |
| Size B [ mm ]                         | 25.5 mm     |

Applications

| Make  |
|-------|
| LEXUS |

Original Code

|             |             |
|-------------|-------------|
| 28100-38021 | 428000-3980 |
| DSN1222     |             |

Equivalent Code (Vehicle Manufacturer)

|                        |                       |
|------------------------|-----------------------|
| 16124 (DELCO)          | 190.917.092 (PSH)     |
| S131.371 (PSH)         | S145.541 (PSH)        |
| 19044R (WAI / TRANSPO) | 20432604OE (REAL)     |
| 255519D (KUHNER)       | 28100-38020 (TOYOTA)  |
| 28100-38021 (TOYOTA)   | 28100-38030 (TOYOTA)  |
| 28100-38031 (TOYOTA)   | 2810038060 (TOYOTA)   |
| 6040406 (SANDO)        | 91-29-5748 (WILSON)   |
| CST40406GS (CASCO)     | DENDSN1222 (WOODAUTO) |
| S-80402 (DIXIE)        | UD104398S (AS-PL)     |
| UD12050S (AS-PL)       | 336524 (LOGISTIK)     |
| STR6542 (ELECTROLOG)   |                       |