



Specifications

| Specification                         | Value    |
|---------------------------------------|----------|
| No./teeth                             | 10 qty   |
| Power                                 | 2.5 kW   |
| No./mount. holes [ qty. ]             | 2 qty    |
| O.1 [ mm ]                            | 127 mm   |
| No./mount. holes with thread [ qty. ] | 0 qty    |
| C.1 [ mm ]                            | 11.00 mm |
| L.1 [ mm ]                            | 300 mm   |
| Voltage                               | 12 V     |
| Rotation                              | CW       |
| C.2 [ mm ]                            | 11.00 mm |
| Size A [ mm ]                         | 89 mm    |
| Size B [ mm ]                         | 47 mm    |

Applications

| Make | Vehicle |
|------|---------|
| JOHN | DEERE   |

Original Code

|             |             |
|-------------|-------------|
| 18456       | 228000-0841 |
| 228000-0844 | RE50165     |

Equivalent Code (Vehicle Manufacturer)

|                       |                         |
|-----------------------|-------------------------|
| S6444S (AS-PL)        | UD19278S (AS-PL)        |
| DENDSN2060 (WOODAUTO) | STR70006 (WOODAUTO)     |
| 91-29-5322 (WILSON)   | 254628 (KUHNER)         |
| 254628D (KUHNER)      | 630.525.102.050 (PSH)   |
| 630.525.102.261 (PSH) | S134.392 (PSH)          |
| S144.627 (PSH)        | CST40448AS (CASCO)      |
| RE50165 (JOHN DEERE)  | RE540301 (JOHN DEERE)   |
| RE54091 (JOHN DEERE)  | RE59588 (JOHN DEERE)    |
| TY24436 (JOHN DEERE)  | 115314 (CARGO)          |
| F032115314 (CARGO)    | 20432844BN (REAL)       |
| 6040448.0 (SANDO)     | 18456N (WAI / TRANSPO)  |
| 190-25111 (ROBERT'S)  | 190-25111NOE (ROBERT'S) |
| STN5314 (KRAUF)       | 246-25173 (DIXIE)       |
| PRSS593 (3EFFE)       | STRS593 (3EFFE)         |
| S12DE0707A2 (SIDAT)   | 5040635 (MEAT & DORIA)  |
| STR6186 (ELECTROLOG)  |                         |