



Specifications

Specification	Value
No./mount. holes [qty.]	3 qty
O.1 [mm]	126 mm
No./mount. holes with thread [qty.]	0 qty
L.1 [mm]	316 mm
Rotation	CW
Size A [mm]	92 mm
Size B [mm]	47.5 mm
No./teeth	10 qty
Power	4 kW
O.3 [mm]	126 mm
Oil sealed	Yes
O.2 [mm]	126 mm
C.1 [mm]	14.00 mm
Voltage	12 V
C.3 [mm]	14.00 mm
C.2 [mm]	14.00 mm

Applications

Make
INTERNATIONAL

Original Code

18406	2-2356-ND-1
228000-5600	228000-8510

Equivalent Code (Vehicle Manufacturer)

18406N (WAI / TRANSPO)	18406R (WAI / TRANSPO)
190-30100 (ROBERT'S)	193432A1 (CASE)
193432A2 (CASE)	20432123BN (REAL)
20432123OE (REAL)	20432452BN (REAL)
20432452OE (REAL)	246-30118 (DIXIE)
S-8854 (DIXIE)	254667 (KUHNER)
3283813 (CUMMINS)	3283815 (CUMMINS)
3675245RX (CUMMINS)	3675246RX (CUMMINS)
3675288RX (CUMMINS)	3920328 (CUMMINS)
3957589 (CUMMINS)	3957590 (CUMMINS)
6040254.0 (SANDO)	6040254.1 (SANDO)
6040321.0 (SANDO)	6040321.1 (SANDO)
87413501 (NEW HOLLAND)	88213771 (POWERMAX)
91-29-5449 (WILSON)	91-29-5449N (WILSON)
CST40254AS (CASCO)	CST40254GS (CASCO)
CST40321.AS (CASCO)	CST40321.GS (CASCO)
SG9103 (GHIBAUDI)	STN8510 (KRAUF)
STR70340 (WOODAUTO)	S6333S (AS-PL)
UD16533S (AS-PL)	STR6429 (ELECTROLOG)
STX210082 (STARDAX)	