



Specifications

Specification	Value
No./mount. holes [qty.]	3 qty
O.1 [mm]	89 mm
No./mount. holes with thread [qty.]	0 qty
L.1 [mm]	279 mm
Rotation	CW
Size A [mm]	89 mm
Size B [mm]	47.5 mm
No./teeth	10 qty
Power	4.8 kW
O.3 [mm]	89 mm
O.2 [mm]	127 mm
C.1 [mm]	11.50 mm
Voltage	12 V
C.3 [mm]	11.50 mm
C.2 [mm]	11.50 mm

Applications

Make	Vehicle
JOHN	DEERE

Original Code

428000-5740	428000-7340
RE537515	

Equivalent Code (Vehicle Manufacturer)

20432884BN (REAL)	20432884OE (REAL)
246-31112 (DIXIE)	S-80600 (DIXIE)
256300D (KUHNER)	6040488.0 (SANDO)
6040488.1 (SANDO)	AI-80085 (AINDE)
CST40488AS (CASCO)	CST40488GS (CASCO)
RE537515 (JOHN DEERE)	RE539696 (JOHN DEERE)
RE541093 (JOHN DEERE)	RE548692 (JOHN DEERE)
RE548694 (JOHN DEERE)	RE549229 (JOHN DEERE)
SE502558 (JOHN DEERE)	STN4740 (KRAUF)
S6427S (AS-PL)	UD18559S (AS-PL)
630.533.103.050 (PSH)	630.533.103.260 (PSH)
S134.098 (PSH)	S144.028 (PSH)
S12DE0708A2 (SIDAT)	5040636 (MEAT & DORIA)
STR6323 (ELECTROLOG)	1906387 (CUMMINS)