



Specifications

Specification	Value
No./mount. holes [qty.]	3 qty
O.1 [mm]	89 mm
No./mount. holes with thread [qty.]	0 qty
L.1 [mm]	318 mm
Rotation	CW
Size A [mm]	89 mm
Size B [mm]	48 mm
No./teeth	10 qty
Power	5.5 kW
O.3 [mm]	127 mm
O.2 [mm]	89 mm
C.1 [mm]	11.50 mm
Voltage	24 V
C.3 [mm]	11.50 mm
C.2 [mm]	11.50 mm

Applications

Make
CATERPILLAR

Original Code

128000-5730	1688125
17616	2-3233-2W

Equivalent Code (Vehicle Manufacturer)

110944 (CARGO)	F032110944 (CARGO)
17616N (WAI / TRANSPO)	20432806BN (REAL)
20930 (KUHNER)	0R4317 (CATERPILLAR)
1119861 (CATERPILLAR)	1688125 (CATERPILLAR)
204-9742 (CATERPILLAR)	3E5381 (CATERPILLAR)
6T0380 (CATERPILLAR)	7C5731 (CATERPILLAR)
8C4773 (CATERPILLAR)	8C4774 (CATERPILLAR)
8C4775 (CATERPILLAR)	9W3748 (CATERPILLAR)
9X9955 (CATERPILLAR)	9X9995 (CATERPILLAR)
45-2196 (ELSTOCK)	6040608 (SANDO)
8EA737131-001 (HELLA)	CGB-23544 (AINDE)
CST40608AS (CASCO)	JS930 (HC PARTS)
MAV426080 (SIOM)	STR9118 (WOODAUTO)
STRS638 (3EFFE)	S6025 (AS-PL)
335780 (LOGISTIK)	STR6031 (ELECTROLOG)