



Specifications

Specification	Value
No./mount. holes [qty.]	3 qty
O.1 [mm]	127 mm
No./mount. holes with thread [qty.]	0 qty
L.1 [mm]	288 mm
Rotation	CW
Size A [mm]	89 mm
Size B [mm]	28 mm
No./teeth	12 qty
Power	5 kW
O.3 [mm]	93 mm
O.2 [mm]	81 mm
C.1 [mm]	10.50 mm
Voltage	24 V
C.3 [mm]	10.50 mm
C.2 [mm]	10.50 mm

Applications

Make
MAN

Original Code

30291	51262017263
M008T63271	M8T63271

Equivalent Code (Vehicle Manufacturer)

MITM8T63271 (WOODAUTO)	PREM85R3005SE (WOODAUTO)
STR71352 (WOODAUTO)	255470 (KUHNER)
255470M (KUHNER)	551.548.123.130 (PSH)
551.548.123.136 (PSH)	551.548.123.138 (PSH)
551.548.123.370 (PSH)	S133.534 (PSH)
S145.052 (PSH)	CST35657AS (CASCO)
CST35657GS (CASCO)	45-5334 (ELSTOCK)
51262017263 (MAN)	LRS04171 (LUCAS)
LRS4171 (LUCAS)	11.139.219 (ISKRA / LETRIKA)
AZE4710 (ISKRA / LETRIKA)	IS9517 (ISKRA / LETRIKA)
72524874 (MAHLE)	MS1035 (MAHLE)
M85405 (PRESTOLITE)	M85R3005SE (PRESTOLITE)
30291N (WAI / TRANSPO)	8067 (CEVAM)
336563 (LOGISTIK)	20437756BN (REAL)
20437756OE (REAL)	6035657.0 (SANDO)
6035657.1 (SANDO)	PRSF355 (3EFFE)
STRF355 (3EFFE)	STM7123 (KRAUF)
CGB-21044 (AINDE)	DRS1044 (DELCO)
S5239S (AS-PL)	UD13180S (AS-PL)
UD19642S (AS-PL)	STR5464 (ELECTROLOG)