



Specifications

Specification	Value
No./mount. holes [qty.]	4 qty
O.1 [mm]	140.4 mm
No./mount. holes with thread [qty.]	3 qty
L.1 [mm]	174 mm
Rotation	CW
Size B [mm]	20 mm
No./teeth	11 qty
C.4 [mm]	M10x1.5 mm
Power	1 kW
O.3 [mm]	136 mm
O.2 [mm]	153 mm
C.1 [mm]	M10x1.5 mm
Voltage	12 V
C.3 [mm]	M10x1.5 mm
C.2 [mm]	8.00 mm

Applications

Make
NISSAN

Original Code

23300-0557R	ESW1012
ESW10E7	

Equivalent Code (Vehicle Manufacturer)

S3178S (AS-PL)	UD14914S (AS-PL)
PRSS553 (3EFFE)	STRS553 (3EFFE)
CGB-54487 (AINDE)	AEX1188 (AUTOELECTRO)
AEY3814 (AUTOELECTRO)	115629 (CARGO)
F032115629 (CARGO)	CST15278AS (CASCO)
CST15278GS (CASCO)	3098 (CEVAM)
DRS0885 (DELCO)	DS1995 (DELCO)
12266 (EAI)	25-4487 (ELSTOCK)
220790 (ERA)	220791 (ERA)
GS438279-A (GPARTS)	GS438279V-R (GPARTS)
CS1582 (HC PARTS)	STV4382 (KRAUF)
254739 (KUHNER)	254739V (KUHNER)
LRS03814 (LUCAS)	LRS3814 (LUCAS)
M000T46571ZT (MITSUBISHI)	M0T46571ZT (MITSUBISHI)
23300-00Q3D (NISSAN)	23300-0557R (NISSAN)
23300-0779R (NISSAN)	23300-1071R (NISSAN)
23300-3307R (NISSAN)	23300-3847R (NISSAN)
23300-7970R (NISSAN)	23300-9161R (NISSAN)
88214550 (POWERMAX)	570.568.114.000 (PSH)
570.568.114.340 (PSH)	570.568.114.341 (PSH)
570.568.114.346 (PSH)	570.568.114.440 (PSH)
570.568.114.500 (PSH)	570.568.114.503 (PSH)
570.568.114.505 (PSH)	S133.875 (PSH)
20479872BN (REAL)	20479872OE (REAL)
6015278.0 (SANDO)	6015278.1 (SANDO)
MAV172780 (SIOM)	MAV172780A (SIOM)
31247N (WAI / TRANSP0)	31247N-OE (WAI / TRANSP0)
STR54177 (WOODAUTO)	VAL438279 (WOODAUTO)
VALESW10E7 (WOODAUTO)	8EA011611-661 (HELLA)
STR00038 (ELECTROLOG)	332252 (LOGISTIK)
233001071 (RENAULT)	4539067500 (RENAULT)
4159064700 (MERCEDES)	A4159064700 (MERCEDES)
A4539067500 (MERCEDES)	4539064700 (SMART)
4539065400 (SMART)	A4539064700 (SMART)
A4539065400 (SMART)	STX210317 (STARDAX)
STX210317R (STARDAX)	ASM1648 (APEC)
NPANSM1648 (NAPA)	14130193 (AES)
42005001 (HERTH+BUSS)	