



Specifications

Specification	Value
No./mount. holes [qty.]	3 qty
O.1 [mm]	90 mm
No./mount. holes with thread [qty.]	0 qty
L.1 [mm]	289 mm
Rotation	CW
Size A [mm]	88.5 mm
Size B [mm]	46 mm
No./teeth	11 qty
Power	2.7 kW
O.3 [mm]	90 mm
O.2 [mm]	127 mm
C.1 [mm]	11.00 mm
Voltage	12 V
C.3 [mm]	11.00 mm
C.2 [mm]	11.00 mm

Applications

Make
BOBCAT

Original Code

18486	600189
6685190	TM000A28901

Equivalent Code (Vehicle Manufacturer)

113727 (CARGO)	F032113727 (CARGO)
18486N (WAI / TRANSP0)	254156 (KUHNER)
254156V (KUHNER)	6032116 (SANDO)
60321160 (SANDO)	60321161 (SANDO)
6676957 (BOBCAT)	6685190 (BOBCAT)
7283321 (BOBCAT)	DSL6676957 (BOBCAT)
DSL6685190 (BOBCAT)	8148 (CEVAM)
8213517 (POWERMAX)	88213517 (POWERMAX)
830.549.113 (PSH)	830.549.113.050 (PSH)
830.549.113.120 (PSH)	830.549.113.260 (PSH)
830.549.113.360 (PSH)	830.549.113.440 (PSH)
830.549.113.441 (PSH)	830.549.113.460 (PSH)
830.549.113.510 (PSH)	S135.392 (PSH)
S144.356 (PSH)	9162901 (MAGNETON)
CGB-28901 (AINDE)	CST32116 (CASCO)
CST32116AS (CASCO)	CST32116ES (CASCO)
CST32116GS (CASCO)	CST32116OS (CASCO)
CST32116RS (CASCO)	DRS0104 (DELCO)
MAV341160 (SIOM)	P6685190 (AS-PL)
S3122S (AS-PL)	UD105129S (AS-PL)
UD13167S (AS-PL)	STR54124 (WOODAUTO)
STRS187 (3EFFE)	ANM12324X (ANDEL)
26-5053 (ELSTOCK)	LES0216 (LUCAS)
LRS03889 (LUCAS)	260018 (CQ)
STR0018 (ELECTROLOG)	