



Specifications

Specification	Value
No./mount. holes [qty.]	3 qty
O.1 [mm]	136 mm
No./mount. holes with thread [qty.]	0 qty
L.1 [mm]	370 mm
Rotation	CW
Size A [mm]	100 mm
Size B [mm]	52.5 mm
No./teeth	13 qty
Power	5.5 kW
O.3 [mm]	119 mm
O.2 [mm]	119 mm
C.1 [mm]	13.50 mm
Voltage	24 V
C.3 [mm]	13.50 mm
C.2 [mm]	13.50 mm

Applications

Make
KOMATSU

Original Code

0-23000-1230	0-23000-1231
18106	600-813-3380

Equivalent Code (Vehicle Manufacturer)

111050 (CARGO)	F032111050 (CARGO)
20446206BN (REAL)	20446206OE (REAL)
244-55201B (DIXIE)	244-55201D (DIXIE)
246-30213D (DIXIE)	600-813-3380 (KOMATSU)
600-813-3390 (KOMATSU)	600-813-3391 (KOMATSU)
600-813-3392 (KOMATSU)	600-813-4110 (KOMATSU)
600-813-4111 (KOMATSU)	600-813-4120 (KOMATSU)
600-813-4121 (KOMATSU)	600-813-4122 (KOMATSU)
6008134652 (KOMATSU)	6050602 (SANDO)
91-28-4049 (WILSON)	941.502.133 (PSH)
CGB-91231 (AINDE)	CGB-93160 (AINDE)
CST50602AS (CASCO)	CST50602GS (CASCO)
DRS0253 (DELCO)	MAV526020 (SIOM)
S9161 (AS-PL)	UD11090S (AS-PL)
STR29010 (WOODAUTO)	18106N (WAI / TRANSP0)
UNIT BOM 185-197 (WAI / TRANSP0)	ANM12473X (ANDEL)
335784 (LOGISTIK)	STR8820 (ELECTROLOG)
CQ1151173 (LAUBER)	