



Specifications

Specification	Value
No./mount. holes [qty.]	3 qty
O.1 [mm]	126 mm
No./mount. holes with thread [qty.]	0 qty
L.1 [mm]	412 mm
Rotation	CW
Size A [mm]	92 mm
Size B [mm]	46 mm
No./teeth	12 qty
Power	7.5 kW
O.3 [mm]	126 mm
Oil sealed	Yes
O.2 [mm]	126 mm
C.1 [mm]	17.00 mm
Wet clutch	Yes
Voltage	24 V
C.3 [mm]	17.00 mm
C.2 [mm]	17.00 mm

Applications

Make
KOMATSU

Original Code

0-23000-3290	0-23000-3291
19939	600-813-3550

Equivalent Code (Vehicle Manufacturer)

600-813-3550 (KOMATSU)	600-813-3551 (KOMATSU)
600-813-6410 (KOMATSU)	600-813-6411 (KOMATSU)
600-813-6412 (KOMATSU)	600-813-6421 (KOMATSU)
600-813-6510 (KOMATSU)	600-813-6520 (KOMATSU)
600-813-6521 (KOMATSU)	600-813-6530 (KOMATSU)
600-8913-6411 (KOMATSU)	UD21193S (AS-PL)
STR75211 (WOODAUTO)	91-28-4051 (WILSON)
255204 (KUHNER)	255204N (KUHNER)
255204P (KUHNER)	941.503.123.265 (PSH)
941.503.123.710 (PSH)	S144.572 (PSH)
CST50638GS (CASCO)	20446836OE (REAL)
6050638.1 (SANDO)	19939N (WAI / TRANSP0)
185-23004 (ROBERT'S)	STK3499 (KRAUF)
45-4434 (ELSTOCK)	LRS02761 (LUCAS)
LRS2761 (LUCAS)	CGB-93290 (AINDE)
CGB-93290R (AINDE)	244-75213C (DIXIE)
S-8952 (DIXIE)	