



Specifications

Specification	Value
No./mount. holes [qty.]	3 qty
O.1 [mm]	127 mm
No./mount. holes with thread [qty.]	0 qty
L.1 [mm]	348 mm
Rotation	CW
Size A [mm]	89 mm
Size B [mm]	47 mm
No./teeth	10 qty
Power	3.3 kW
O.3 [mm]	90 mm
O.2 [mm]	90 mm
C.1 [mm]	10.50 mm
Voltage	12 V
C.3 [mm]	10.50 mm
C.2 [mm]	10.50 mm

Applications

Make	Vehicle	Model Types	From	To
INTERNATIONAL	8100 6.0	VT-365	01/2002	12/2006
INTERNATIONAL	4900 6.0	VT-365	01/2002	12/2007
INTERNATIONAL	9100 6.0	VT-365	01/2002	12/2006
INTERNATIONAL	5900 6.0	VT-365	01/2002	12/2006
INTERNATIONAL	3000 6.0	VT-365	01/1999	12/2007
INTERNATIONAL	7700 6.0	VT-365	01/2002	12/2006
INTERNATIONAL	4000 6.0	VT-365	01/2002	12/2007
INTERNATIONAL	8600 6.0	VT-365	01/2002	12/2006
INTERNATIONAL	5000 6.0	VT-365	01/2002	12/2006
INTERNATIONAL	9900 6.0	VT-365	01/2002	12/2006
INTERNATIONAL	7100 6.0	VT-365	01/2002	12/2006
INTERNATIONAL	3900 6.0	VT-365	01/2002	12/2006
INTERNATIONAL	Durastar 6.4		01/2008	12/2015
INTERNATIONAL	TeRastar 6.4		01/2010	12/2013

Original Code (Vehicle Manufacturer)

3804470C92	8200271
8200271 (DELCO)	91-01-4787
M105R2511SE	TS-1811
UD30042S	

Equivalent Code (Vehicle Manufacturer)

3804470C92 (NAVISTAR)	91-01-4787 (WILSON)
M105R2511SE (PRESTOLITE)	TS-1811 (DIXIE)
UD30042S (AS-PL)	