



Specifications

Specification	Value
No./mount. holes [qty.]	3 qty
O.1 [mm]	127 mm
No./mount. holes with thread [qty.]	0 qty
L.1 [mm]	502 mm
Rotation	CW
Size A [mm]	92 mm
Size B [mm]	47.5 mm
No./teeth	12 qty
Power	7.5 kW
O.3 [mm]	127 mm
Oil sealed	Yes
O.2 [mm]	127 mm
C.1 [mm]	16.50 mm
Voltage	12 V
C.3 [mm]	16.50 mm
C.2 [mm]	16.50 mm

Applications

Make	Vehicle
CATERPILI	AR

Original Code

10461021	10461034
OR2189	

Equivalent Code (Vehicle Manufacturer)

640.005.123.030 (PSH)	640.005.123.038 (PSH)
640.005.123.395 (PSH)	640.005.123.710 (PSH)
S134.930 (PSH)	S144.512 (PSH)
STD2436 (KRAUF)	RE41756 (JOHN DEERE)
0R2189 (CATERPILLAR)	0R4260 (CATERPILLAR)
0R4265 (CATERPILLAR)	0R5208 (CATERPILLAR)
0R5216 (CATERPILLAR)	0R5218 (CATERPILLAR)
2N3538 (CATERPILLAR)	3T2655 (CATERPILLAR)
3T2657 (CATERPILLAR)	3T2659 (CATERPILLAR)
6V4215 (CATERPILLAR)	7N6503 (CATERPILLAR)
7T1081 (CATERPILLAR)	7T2265 (CATERPILLAR)
7T9254 (CATERPILLAR)	8C356 (CATERPILLAR)
8C3580 (CATERPILLAR)	8C3596 (CATERPILLAR)
8C3648 (CATERPILLAR)	8L5881 (CATERPILLAR)
9L3597 (CATERPILLAR)	9W0058 (CATERPILLAR)
OR2189 (CATERPILLAR)	OR5208 (CATERPILLAR)
140-42855 (ROBERT'S)	157579 (CUMMINS)
185617 (CUMMINS)	197125 (CUMMINS)
360432312X (CUMMINS)	3604323RX (CUMMINS)
3907622 (CUMMINS)	3910645 (CUMMINS)
3938501 (CUMMINS)	STR80002 (WOODAUTO)
CST60123AS (CASCO)	CST60123GS (CASCO)
20409321BN (REAL)	20409321OE (REAL)
6060123.0 (SANDO)	6060123.1 (SANDO)
25-3300 (ELSTOCK)	LRS01741 (LUCAS)
LRS1741 (LUCAS)	91-01-4161 (WILSON)
M0017276ME (PRESTOLITE)	STRW001 (3EFFE)
S1135 (AS-PL)	UD12391S (AS-PL)
STR2604 (ELECTROLOG)	STR2630 (ELECTROLOG)