



Specifications

Specification	Value
No./mount. holes [qty.]	2 qty
O.1 [mm]	105 mm
No./mount. holes with thread [qty.]	0 qty
L.1 [mm]	340 mm
Rotation	CW
Size A [mm]	82.5 mm
Size B [mm]	33 mm
No./teeth	10 qty
No./teeth (fits into) [qty.]	10 qty
Power	4 kW
C.1 [mm]	12.50 mm
Voltage	24 V
C.2 [mm]	12.50 mm

Applications

Make	Vehicle
JOHN	DEERE

Original Code

10461444	1998519
6596	RE503118

Equivalent Code (Vehicle Manufacturer)

0001368059 (BOSCH)	113007 (CARGO)
F032113007 (CARGO)	255200 (KUHNER)
35259650 (PRESTOLITE)	S5007L (PRESTOLITE)
6010666 (SANDO)	6010708 (SANDO)
6596N (WAI / TRANSPO)	8477R (CEVAM)
CST10666 (CASCO)	CST10666AS (CASCO)
CST10666ES (CASCO)	CST10666GS (CASCO)
CST10666OS (CASCO)	CST10666RS (CASCO)
CST10708 (CASCO)	CST10708AS (CASCO)
CST10708ES (CASCO)	CST10708GS (CASCO)
CST10708OS (CASCO)	CST10708RS (CASCO)
MAV123600 (SIOM)	MAV127080 (SIOM)
RE503118 (JOHN DEERE)	RE51725 (JOHN DEERE)
RE52150 (JOHN DEERE)	RE522738 (JOHN DEERE)
RE67086 (JOHN DEERE)	STR20034 (WOODAUTO)
STRJ314 (3EFFE)	STRJ675 (3EFFE)
STRL842 (3EFFE)	STR10314 (ELECTROLOG)
STR2076 (ELECTROLOG)	6000734 (LIEBHERR)