



Specifications

Specification	Value
No./mount. holes [qty.]	3 qty
O.1 [mm]	127 mm
No./mount. holes with thread [qty.]	0 qty
L.1 [mm]	418 mm
Rotation	CW
Size A [mm]	92 mm
Size B [mm]	48 mm
No./teeth	12 qty
No./teeth (fits into) [qty.]	12 qty
Power	7.8 kW
O.3 [mm]	127 mm
Oil sealed	Yes
O.2 [mm]	127 mm
C.1 [mm]	16.50 mm
Voltage	24 V
C.3 [mm]	16.50 mm
C.2 [mm]	16.50 mm

Applications

Make
CUMMINS

Original Code

5284105	6823
8200101	8200435

Equivalent Code (Vehicle Manufacturer)

S1028 (AS-PL)	255569 (KUHNER)
255569D (KUHNER)	255569P (KUHNER)
641.010.123.030 (PSH)	641.010.123.310 (PSH)
641.010.123.380 (PSH)	641.010.123.381 (PSH)
641.010.123.391 (PSH)	S134.932 (PSH)
S144.516 (PSH)	CST11662GS (CASCO)
S24DR0010 (SIDAT)	S24DR0010A2 (SIDAT)
115447 (CARGO)	F032115447 (CARGO)
M105R3523AM (PRESTOLITE)	M105R3523SE (PRESTOLITE)
M105R3541AM (PRESTOLITE)	M105R3541SE (PRESTOLITE)
STRJ385 (3EFFE)	6011662.1 (SANDO)
20412266OE (REAL)	88213411 (POWERMAX)
6823N (WAI / TRANSP0)	STR80185 (WOODAUTO)
5284105 (CUMMINS)	5284106 (CUMMINS)
339025 (LOGISTIK)	141733 (PIC)
6823 (LESTER)	CU5284105 (KOMATSU)
339-5406 (CATERPILLAR)	STR2654 (ELECTROLOG)