



Specifications

Specification	Value
No./mount. holes [qty.]	3 qty
O.1 [mm]	126 mm
No./mount. holes with thread [qty.]	0 qty
L.1 [mm]	413 mm
Rotation	CW
Size A [mm]	92 mm
Size B [mm]	48 mm
No./teeth	12 qty
Power	8.3 kW
O.3 [mm]	126 mm
Insulated return	Yes
O.2 [mm]	126 mm
C.1 [mm]	13.50 mm
Voltage	24 V
C.3 [mm]	13.50 mm
C.2 [mm]	13.50 mm

Applications

Make
CATERPILLAR

Original Code

10461758	10479276
6803	7T0800

Equivalent Code (Vehicle Manufacturer)

114013 (CARGO)	F032114013 (CARGO)
140-39118 (ROBERT'S)	2-2349-DR-1 (WAI / TRANSP0)
6803N (WAI / TRANSP0)	6803R (WAI / TRANSP0)
201-39202 (DIXIE)	TS-1748 (DIXIE)
20409906BN (REAL)	20409906OE (REAL)
3102767 (CUMMINS)	6060609.0 (SANDO)
6060609.1 (SANDO)	91-01-4572 (WILSON)
91-01-4572N (WILSON)	CGB-1748 (AINDE)
CST60609AS (CASCO)	CST60609GS (CASCO)
MAV626090 (SIOM)	STD4013 (KRAUF)
STD6913 (KRAUF)	STD8913 (KRAUF)
STP4013 (KRAUF)	STR0274 (3EFFE)
STR80007 (WOODAUTO)	UD12365S (AS-PL)
STR2689 (ELECTROLOG)	7T0800 (CATERPILLAR)
STX201301 (STARDAX)	