



Specifications

Specification	Value
No./mount. holes [qty.]	3 qty
O.1 [mm]	103 mm
No./mount. holes with thread [qty.]	0 qty
L.1 [mm]	321 mm
Rotation	CW
Size A [mm]	92 mm
Size B [mm]	21 mm
No./teeth	10 qty
Power	3 kW
O.3 [mm]	103 mm
O.2 [mm]	146 mm
C.1 [mm]	11.00 mm
Voltage	12 V
C.3 [mm]	11.00 mm
C.2 [mm]	11.00 mm

Applications

Make
FORD

Original Code

82013134	AZF4115
IS1016	

Equivalent Code (Vehicle Manufacturer)

S9225 (AS-PL)	UD11316S (AS-PL)
9007044014 (BOSCH)	CST21109AS (CASCO)
CST21109GS (CASCO)	82015723 (CASE)
87318759 (CASE)	87653221 (CASE)
11327170 (CLAAS)	DRS0985 (DELCO)
25-3166 (ELSTOCK)	82013134 (FORD)
82014160 (FORD)	82021372 (FORD)
82021372C (FORD)	84017265 (FORD)
8775550R (FORD)	87755550 (FORD)
87755550C (FORD)	87755550R (FORD)
STI4183 (KRAUF)	18024 (LESTER)
19653 (LESTER)	331815 (LOGISTIK)
LRS01637 (LUCAS)	LRS1637 (LUCAS)
72735878 (MAHLE)	MS25 (MAHLE)
88213173 (POWERMAX)	590.554.103.090 (PSH)
590.554.103.311 (PSH)	S134.516 (PSH)
S144.721 (PSH)	20419901BN (REAL)
20419901OE (REAL)	6021109.0 (SANDO)
6021109.1 (SANDO)	S12ML0370A2 (SIDAT)
91-23-6522 (WILSON)	MAHMS25 (WOODAUTO)
STR60603 (WOODAUTO)	5065803 (MEAT & DORIA)
STR7898 (ELECTROLOG)	