



Specifications

Specification	Value
No./teeth	10 qty
Power	3.2 kW
No./mount. holes [qty.]	2 qty
O.1 [mm]	105 mm
No./mount. holes with thread [qty.]	0 qty
C.1 [mm]	11.00 mm
L.1 [mm]	276.5 mm
Voltage	12 V
Rotation	CW
C.2 [mm]	11.00 mm
Size A [mm]	82.5 mm
Size B [mm]	34 mm

Applications

Make	Vehicle
JOHN	DEERE

Original Code

AZE4185	IS1059
RE501347	

Equivalent Code (Vehicle Manufacturer)

UD13625S (AS-PL)	116379 (CARGO)
F032116379 (CARGO)	RE501347 (JOHN DEERE)
RE501680 (JOHN DEERE)	RE501689 (JOHN DEERE)
RE501693 (JOHN DEERE)	RE501713 (JOHN DEERE)
RE502156 (JOHN DEERE)	RE502196 (JOHN DEERE)
RE506589 (JOHN DEERE)	RE508736 (JOHN DEERE)
RE516455 (JOHN DEERE)	RE519568 (JOHN DEERE)
RE519975 (JOHN DEERE)	RE551444 (JOHN DEERE)
RE60641 (JOHN DEERE)	RE62916 (JOHN DEERE)
RE63010 (JOHN DEERE)	SE501854 (JOHN DEERE)
SE501869 (JOHN DEERE)	72736058 (MAHLE)
MS430 (MAHLE)	630.538.102.090 (PSH)
630.538.102.098 (PSH)	630.538.102.310 (PSH)
S134.181 (PSH)	S144.177 (PSH)
91-23-6545 (WILSON)	MAHMS430 (WOODAUTO)
STR60682 (WOODAUTO)	STR7961 (ELECTROLOG)
STX200819 (STARDAX)	